

RHM162

ALPHA HD 16CH All in one DVR



Specifications

DVR Model		RHM162
Video Input	No. of channel	16ch / BNC
Video Output	Monitor	1ch HD Output, 1ch VGA, 1ch Spot
Multitasking		Quadplex (Live, Play, Network, Record)
Recording	Resolution	1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x480, 960x240, 480x240 (NTSC) 1920x1080, 1920x540, 960x540, 1280x720, 1280x360, 640x360, 960x576, 960x288, 480x288 (PAL)
	Max. speed	240fps at 1080P (NTSC) 200fps at 1080P (PAL)
	Mode	Schedule, Event (Sensor, Motion detection), Manual, Continuous, Continuous+Event
Display	Resolution	1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080
Search	Mode	Quick, Calendar, Bookmark, Event (Sensor, Motion detection), USB
Playback	Speed	x1, x2, x4, x8, x16, x32, x64, x128, x256, field by field (forward, backward) X1/4, x1/2 Slow Motion (forward only), Repeat A-B
Video Input		TVI / AHD / CVI / Composite Video BNC (960H and 2CH IP Video)
Audio Input		4ch
Audio Output		1ch
Sensor Input		4 (NO/NC selectable)
Alarm Output (Relay)		1 Relay Output
Network	Speed & Type	10/100M/1G (16ch only) (Static, DHCP, UPnP), E-mail, DDNS server available
	Codec	Dual Codec. (H.264)
	Bandwidth Limit	Yes
Storage	SATA	HDD 2EA (Max. 20TB)
Backup		USB Flash Memory, Network, USB HDD
Password Protection		1 admin + 100 users
Interface	PTZ Control	RS-485
S/W Upgrade		USB Flash Memory
Power Source & Consumption		+12VDC / 4A Adaptor (100 ~ 240VAC, 50Hz/60Hz, 60W)
Dimension (mm)		320(W) x 330(D) x 70(H)
Option		Rack Mount Support
VMS / Mobile Monitor		Support (RHM Client) / Supports Android phone/iPhone/iPad (RHM Viewer)