

ANCHOR V (for hand welding)

V1




V4




FOR HAND WELDING

V1



Refractory castable

V4



* : OPTION: see page C2-03 & C2-04
C2-06 & C2-07

IRIS manufactures anchors from cold drawn wires, with a specific tensile strength, using a "soft bending technique", utilizing robotic machines. This "in house" developed technology, reduces mechanical stress in the steel structure and avoids the formation of micro cracks, through which corrosion can accelerate and damage the anchors.

Due to the advanced bending methods developed by IRIS, there are mostly no bending marks in our metal anchors.



IRIS - Industrial Refractories & Insulating Specialities

Parc d'Activités Aérodrome Ouest - Rouvignies - F - 59328 VALENCIENNES Cedex (France)

Tél : +33 (0)3.27.21.52.80

E-mail: contact@irisfrance.com

Fax : +33 (0)3.27.21.52.99

Web: www.irisfrance.com

This drawing is the property of IRIS. Unauthorised use of patented features and/or reproduction of this drawing is strictly prohibited.

DESIGNATION EXAMPLE V1.6(60) - 040 - 304

Anchor type Angle Length L Alloy
 Diameter D

V1

OPTION CAPS:


UV.6(80/90)- 050/040 - 309 -C

Polyethylene caps on top of anchors allow to avoid stress and possible cracks, spalling due to the thermal expansion of steel higher than castable expansion.

N.B: basic plastic is mainly PVC.
C is chlorine which is not good for the CaO of the castable.


OPTION LENGTH L1+L2

For unequal legs



Notes:

Most frequent angles : 45°-60°-90°
any angle on request.




*Sketch not contractual

IRIS manufactures anchors from cold drawn wires, with a specific tensile strength, using a "soft bending technique", utilizing robotic machines. This "in house" developed technology, reduces mechanical stress in the steel structure and avoids the formation of micro cracks, through which corrosion can accelerate and damage the anchors.

Due to the advanced bending methods developed by IRIS, there are mostly no bending marks in our metal anchors

OPTIONS

CH .BL (bent legs)



With top of legs bent

DESIGNATION: CH1.BL.8(60)-085-310-BL=25

CH .ON (On standard Nut)



Welded on Nut

DESIGNATION: CH1.6(60)-100-310-ON-M8-310


	Height standard Nut (mm)	Height high Nut (mm)
M6	5	6
M8	6,5	8
M10	8	10
M12	10	12

CH .OB (On Boss)


Welded on boss

DESIGNATION: CH1.6(60)-100-310-OB-M8-310

dimension Boss:
M6 : Ø10 ext.
M8 : Ø12 ext.
M10 : Ø14 ext.
M12 : Ø16 ext.



CH .OS (On Stud)




Welded on threaded stud

DESIGNATION: CH1.6(60)-100-310-OS-M6-20-310

WB . 8 , R12 / 25 - 310


Anchor type Ø D Radius R Length L

Alloy and length to detail.



IN.BSP.040.040.8(10) - 304

Alloy and length to detail.



DESIGNATION EXAMPLE V4.6(60) - 060 - 304

Anchor type Angle Length L Alloy

Diameter D

V4

OPTION CAPS:

UV.6(80/90)- 050/040 - 309 -C

Polyethylene caps on top of anchors allow to avoid stress and possible cracks, spalling due to the thermal expansion of steel higher than castable expansion.

N.B: basic plastic is mainly PVC.

C is chlorine which is not good for the CaO of the castable.


OPTION LENGTH L1+L2

For unequal legs



Notes:

Most frequent angles : 45°-60°-90°
any angle on request.




*Sketch not contractual

IRIS manufactures anchors from cold drawn wires, with a specific tensile strength, using a "soft bending technique", utilizing robotic machines. This "in house" developed technology, reduces mechanical stress in the steel structure and avoids the formation of micro cracks, through which corrosion can accelerate and damage the anchors.

Due to the advanced bending methods developed by IRIS, there are mostly no bending marks in our metal anchors.

OPTIONS

CH .BL (bent legs)



With top of legs bent

DESIGNATION: CH1.BL.8(60)-085-310-BL=25

CH .ON (On standard Nut)

Welded on Nut

DESIGNATION: CH1.6(60)-100-310-ON-M8-310


	Height standard Nut (mm)	Height high Nut (mm)
M6	5	6
M8	6,5	8
M10	8	10
M12	10	12

CH .OB (On Boss)


Welded on boss

DESIGNATION: CH1.6(60)-100-310-OB-M8-310

dimension Boss:
M6 : Ø10 ext.
M8 : Ø12 ext.
M10 : Ø14 ext.
M12 : Ø16 ext.



CH .OS (On Stud)




Welded on threaded stud

DESIGNATION: CH1.6(60)-100-310-OS-M6-20-310

WB . 8 , R12 / 25 - 310

Anchor type Ø D Radius R Length L

Alloy and length to detail.



IN.BSP.040.040.8(10) - 304

Alloy and length to detail.

