

PW240

Pressure Washers - PW series



Direct Transmission

Main features

| | | |
|--------------------|---------|------|
| Max pressure | bar | 240 |
| Max pressure | psi | 3500 |
| Flow | l/min | 13 |
| Flow | gal/min | 3 |
| Certification mark | | CE |

Engine specifications

| | | |
|-----------------|-----------------|--------|
| Model | | GX390 |
| Displacement | cm ³ | 389 |
| Fuel | | Petrol |
| Starting system | | Recoil |

Pump specifications

| | | |
|----------------|-------|---------------------|
| Manufacturer | | Annovi Reverberi |
| Model | | GRKV 4 G35 H |
| Type | | Triplex plunger |
| Rotation speed | rpm | 3400 |
| 1.3 Drive | | Direct |
| Max pressure | bar | 240 |
| Max flow | l/min | 15.1 |

Dimensional data

| | | |
|-------------------------|----|-----|
| Length with trolley | mm | 951 |
| Width with trolley | mm | 765 |
| Height with trolley | mm | 655 |
| Dry weight with trolley | Kg | 64 |

Consumption, running time and noise

| | | |
|------------------------------|-------|-----|
| Fuel tank capacity | l | 6.1 |
| Running time | h | 3.0 |
| Noise level at 7 m | dB(A) | 78 |
| Guaranteed noise level (LWA) | dB(A) | 103 |

Standard equipment

| | |
|-----------------------|----------|
| Transportation kit | Standard |
| Direct drive | Standard |
| Oil guard | Standard |
| Lance pressure washer | Standard |
| Chemical injection | Standard |
| Pressure hose | Standard |
| Inline filter | Standard |



Printed on 2/10/2015 (ID 738)

©2012 | PR INDUSTRIAL s.r.l. | All rights reserved | Image shown may not reflect actual package.
Specifications subject to change without notice | ENERGY GENERATION is registered trademarks of
PR INDUSTRIAL s.r.l. Other company, product or service names may be trademarks or service marks
of others. RevA (06/2012).

