



10 Inch LCD display and built-in wireless video NVR

SPECIFICATION

MODEL No.	WKM-334
Operating System	Embedded Linux operating system
VIDEO/IMAGE	
Image Code Control	Image code quality adjustable, variable bitstream and constant bitstream optional
Dual Stream	
Video Standard	720P/960P/1080P
Monitoring Image Quality	720P/960P/1080P
Image Motion Detection	Each screen can set mutiple detection areas and set 6-level sensitivity (IPC Support)
Recording Playback Quality	4ch playback simultaneously
Recording Mode	Support manual, auto, dynamic detection, alarm trigger record mode
Backup Way	Support U disk, USB mobile HDD, USB DVD-RW, network storage and backup
Recording Storage	Local HDD, network
LCD Screen	
Display Size	10.1 inch
Resolution	1024(H) * 600 (V)
Luminance	250cd/m ³
VIDEO INPUT	
IP Video Input	4*720P/960P/1080P IP camera
VIDEO OUTPUT	
HDMI Output	No
VGA Output	No
AUDIO	
Audio Compression	G.711A
Voice monitoring	Optional
ALARM MANAGEMENT	
Events Trigger	Built-in motion detection, schedule
Notification Method	Alarm, Buzzer, E-mail, FTP

WIRELESS	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Signal Rate	Up to 300Mbps
Frequency Range	2.4-2.4835GHz
Transmit Power	<24dBm
Modulation Mode	802.11b: CCK, QPSK, BPSK 802.11g/n: OFDM
HARD DISK	
Interface Type	1* SATA interface
Capacity	Support up to 4TB SATA HDD for update
INTERFACES	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Network Interfaces	1* 10/100Mbps Auto MDI/MDIX RJ45 WAN port
USB Interface	1* USB 2.0 Port
LED Indicators	Power, Hard Disk ,RUN
Antennas	2* 5dBi Detachable Antenna, SMA Connector
Power Supply	DC 12V/2A (Output)
SOFTWARE	
WAN Type	DHCP, Static IP, PPPoE
Port Forwarding	Virtual Servers, Port Triggering, UPnP (play&plug), DMZ, FTP Private Port
LAN	DHCP Client, DHCP Server
Mobile Surveillance	Support iPhone, Android smart phone for remote control
Others	Time Settings,Firmware Upgrade, Backup & Restore
GENERAL	
Environment	Operating Temperature: -10℃~55℃
	Storage Temperature: -40℃~70℃
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Dimensions(L x W x H)	288 (W) x 252 (H) MM (with stand)