



Model No: HW0054

System	System Security	Supports three-level account, password, user authority management.
	OS	Embedded Linux OS
	Processor	Hi3516C
	P2P (Free)	No need to preset camera, Offer free P2P(ZZZZ-xxxxxx-xxxxx), Plug&play, Support QR code scanning to view
	Onvif Protocol	Support ONVIF Protocol
	Multi-device function	Support 12 language remote surveillance, record, alarm, wifi setting etc.
	PC client	Support remote multi-devices monitor, record, alarm etc;Support windows and mac os
	Cell Phone View	Self R&D APP, Support Iphone,Android smart Phone
	TF Card Record	Support max 128GB,
Lens	Lens Type	2.8-12MM
	IR-CUT	Build-in IR CUT, no color cast,auto switch when IR on
Video	Image Compression	H.264/MJPEG
	Sensor	1/2.7" Progressive Scan 2MP CMOS
	Video Parameters	Brightness, Contrast,Saturation,Exposure,sharpness can be adjusted
	Image Frame Rate	50Hz:25fps/60HZ:30fps (1920×1080)
	First Stream	1080P(1920×1080),720P (1280x720)
	Second Stream	VGA-(640x352),(320x176)
Audio	Compression format	G.711 (G.711 Default)
	Audio In	Built in Mic
	Audio Out	Built in Speaker
Night Vision	Night Visibility	3 array Led lights,night vision is up to 50m
	Lux	IR ON 0 LUX
Pan/Tilt	Preset	Support 8 Preset Positions
	Rotation Angle	Pan:355°, Tilt: 90°
	Rotation Speed	Pan: Speed Range 5-50°/ S; Tilt: Speed Range 5-30°/ S;
Alarm	Motion Detect	Support 4 Independent detection areas(Sensitivity can be adjustd 1-100)
	Alarm Action	Support Email Photo Alert,Snapshot and Record uploaded to FTP
	Ethernet Interface	One 10/100Mbps RJ-45

Network	Supported Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP etc.
	Online Visitor	Support Max 6 visitors at the same time (First Stream:3 visitors;Second Stream:3 visitors)
	IP Mode	Dynamic IP address, static IP address (DHCP)
	Online Visitor	Support Microsoft Win XP/Win7/Win8/ win10/Mac OS.
	Browser	Support Internet Explorer 8.0-11.0, FireFox, Google Browser
	One key setting Function	Support one key setting function connect WIFI
	Wireless Standard	WIFI, 802.11b/g/n
Others	OSD	Support the OSD name, date and time info superposition (Open/Off)
	Product Type	Cartoon Robot/ Indoor use
	Power	DC12V/2A
	Working Temperature	-10~50 °C
	Working Humidity	95% RH
	Size	Item:184*130*108mm (HxW); Packaging: 203*203*134mm (LxWxH)
	Weight	N.W.: 886.5g G.W.: 1.24kg(Note:Actual Weight Final)
	Accessories	Adaptor,Screws*3,User manual,1m Ethernet Cable*1
Certification	CE,FCC,RoHS	
Warranty	Limited 2-Year Warranty	