## ThinkPad T480 Platform Specifications

Processor	7th Generation Intel® Core™ i5 Processor								Dimensions	WxDxH: 13.25" x 9.15" x 0.79"; 336.6mm x 232.5mm x 19.95mm			
									Weight	Models		24Wh or 24Wh + 24Wh	48Wh, 72Wh, or 24Wh + 48Wh / 72Wh
	Number		Threads	Frequency	Frequency		Types	Graphics		Integrated Ma	gnesium	3.49 lb / 1.58 kg	3.92 lb / 1.78 kg
	i5-7200U	2	4	2.5 GHz	3.1 GHz 3MB	DDR4-2133	Intel HD Graphics		Integrated PP		3.63 lb / 1.65 kg	4.08 lb / 1.85 kg	
	i5-7300U			2.6 GHz	3.5 GHz	3MB	BB111 2100	620	_	Discrete Magn		3.53 lb / 1.60 kg	3.97 lb / 1.80 kg
	or 8th Generation Intel Core i5 / i7 Processor									Discrete PPS 3.68 lb / 1.67 kg 4.12 lb / 1.87 kg			
	Processor Number	ber Cores Threads Frequency Frequency Cache Types					Processor Graphics	Case color Case material	Black  Display cover: Magnesium Hybrid or PPS;  Bottom: Glass-Fiber Reinforced Plastic				
	i3-8130U i5-8250U i5-8350U i7-8550U i7-8650U	2 4	8	2.2 GHz 1.6 GHz 1.7 GHz 1.8 GHz 1.9 GHz	3.4 GHz 3.4 GHz 3.6 GHz 4.0 GHz 4.2 GHz	4MB 6MB 6MB 8MB	DDR4-2400	Intel UHD Graphics 620		r Optional: Smart card reader 4-in-1 reader (MMC, SD, SDHC, SDXC) Two USB 3.1 Gen 1 (one Always On), USB 3.1 Type-C Gen 1, USB 3.1 Type-C Gen 2 / Thunderbolt 3, HDMI 1.4b, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack,			
Graphics	Intel HD Graphics 620 or Intel UHD Graphics 620 in processor only or Intel HD Graphics 620 or Intel UHD Graphics 620 in processor and NVIDIA® GeForce® MX150, 2GB GDDR5 memory; supports external digital monitor via HDMI or USB Type-C; supports three independent displays;								Monitor cable (optional) Camera (optional)	optional smart card reader, 4-in-1 reader (MMC, SD, SDHC, SDXC), side docking connector, security keyhole USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter  One of the following, configurable by model:			
Chipset Memory	Max resolution: 4096x2304@60Hz (USB Type-C); 4096x2160@30Hz (HDMI)  Intel SoC (System on Chip) platform 32GB max / 2400MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets * System clocks down for processors with lower memory controller								Audio support	<ul> <li>HD720p camera with ThinkShutter camera privacy, fixed focus</li> <li>IR camera and HD720p camera, fixed focus</li> <li>HD Audio, Realtek® ALC3287 codec, Dolby® Audio™ Premium / stereo speakers, 2W x 2 / dual array microphone, headphone / microphone combo jack</li> </ul>			
Display	Some: 14.0" (355mm) HD (1366x768), anti-glare, LED backlight, 220 nits, 16:9 aspect ratio, 400:1 contrast ratio  Some: 14.0" (355mm) FHD (1920x1080), anti-glare, LED backlight, IPS, 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing angle  Some: 14.0" (355mm) WQHD (2560x1440), anti-glare, LED backlight, IPS, 300 nits, 16:9 aspect ratio, 700:1 contrast ratio, 72% gamut, 170° viewing angle  On-cell touch, supports 10-finger gesture (FHD only)								Keyboard UltraNav™	6-row, spill-re TrackPoint®p	esistant, r pointing d	multimedia Fn keys, opti evice and buttonless My	onal LED backlight rlar surface multi-touch touchpad
Multi-touch (opt)									Security Power-on password, hard disk password, supervisor password, security keyhole Security chip Discrete TPM 2.0, TCG Certified vPro (optional) Intel vPro Technology Fingerprint reader Optional: Touch style match on chip fingerprint reader on the keyboard bezel, anti-spoofing technology NFC (optional) Near Field Communication				
Storage	System has one HDD slot or one M.2 2280 slot exclusively for storage Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™ Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD) Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: 128GB M.2 SSD / PCIe NVMe, PCIe 3.0 x 2, 16Gb/s,								Battery Max battery life (MobileMark® 2014)	ALA COLLA			h + 24Wh   24Wh + 48Wh   24Wh + 72Wh
Online	in WWAN slot as 2nd Storage, mutually exclusive with WWAN Some: 16GB Intel Optane™ memory, PCIe NVMe, PCIe 3.0 x 2, 16Gb/s, in WWAN slot as storage cache for HDD, mutually exclusive with WWAN								AC adapter	discrete model   6.6 hr   13.2 hr   19.8 hr   13.6 hr   19.8 hr   26.4 hr    * Battery life varies significantly with settings, usage, & other factors 45W or 65W USB Type-C AC adapter			
Optical	None								Preload	Windows® 10	O Home 6	4 or Windows 10 Pro 64	1
Ethernet	vPro model: Intel Ethernet Connection I219-LM (Jacksonville)							,	Limited warranty	One of the following, configurable by model:  1-year depot repair service			
WLAN + Bluetooth™	Intel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card * Intel 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS						lows OS		3-year/1-yr battery depot repair service     3-year/1-yr battery limited onsite service				
WWAN (optional)	- Interveted Makile Dysadlessed 40 LTC								Mil-Spec test	MIL-STD-81	0G militar	ry certification	
SIM card (opt)									Environment	vironment EPEAT™ Gold; ENERGY STAR® 6.1; RoHS-compliant			
Silvi Caru (Opt)	Nano-SIIV	i card s	iot, optio	niai verižor	LIE (08) 8	onvi ca	ru						Lenov