

# THE CARBON TWIN A New Generation

### Infrared Heating Technology

Infrared emitters transmit large amounts of energy in a short time and at high efficiency. The wavelength of the infrared radiation has a crucial effect on the effectiveness of the heating process. Infrared emitters, which are optimally matched to the materials to be heated, provide energy savings of up to 50%. Heraeus infrared heating technology offers significant advantages: heat exactly where it is needed, with the optimum wavelength for the product and in line with the process.

### **The Combined Advantages**

The new generation of proven Heraeus twin tube emitters is the Carbon Twin. Its maximum power density is twice that of conventional twin tube emitters, perfect for

- fast drying of waterbased inks and lacquers,
- economical processing of plastics and glass.

Twin tube carbon emitters can be easily retrofitted into existing infrared systems. They replace the existing emitters, improve the system and decrease the running costs.

## The Carbon TWIN

In the medium wave range, Heraeus offers tailor-made twin tube emitters or carbon round tube emitters of especially high efficiency.

New is the unique combination of both of these technologies, which allows important synergy effects.

Common to both types of emitters is the medium wave spectrum. Many materials absorb infrared especially in this region of the spectrum. The use of infrared emitters therefore contributes to the accelerated drying of water and other solvents and to economical processing of plastics and glass.

The proven twin tube emitters bring their high stability to the carbon twin, as well as a significantly increased radiation density. In addition, they offer the possibility of manufacture in a range of models and the emitters can be connected to conventional standard mains supplies.

The carbon emitter technology contributes to the high power density of the carbon twin. Carbon emitters have twice the maximum power density of conventional medium wave twin tube emitters. In addition, carbon emitters have fast heat-up and cool-down times and can be switched on and off in seconds.



2

0

F

5

70

LU.

5

F

×

>

>

>

2

0

u

0

L)


2 4

ک

L

Z





Spectrum of the Carbon Twin infrared emitter compared with other Heraeus infrared emitters - taken at the same electrical power for all emitter types.

## **HERAEUS**

is market leader for tailor-made infrared emitters. We provide individual customer advice and offer an Application Centre for your tests. We have the optimum spectrum for your application

- Infralight halogen infrared emitters
- Twin tube infrared emitters in all relevant wavelengths
- MagicHeat Carbon infrared emitters
- Infrared modules and controls for industrial applications
- Emitters for targeted heating in finishing processes.

Standard designs for Carbon twin tube emitters (A, B, C, D)

Specifications are subject to change without notice.



Heraeus Noblelight GmbH Reinhard-Heraeus-Ring 7 D-63801 Kleinostheim Germany Phone +49 (6027) 507-407 Telefax +49 (6027) 507-410 E-Mail:

hng-infrared@europe.heraeus.com Internet: www.heraeus-noblelight.com Heraeus Noblelight Ltd. 8, Caldbeck Road Bromborough, Wirral Merseyside L62 3PL/England Phone +44 (151) 343 0545 Telefax +44 (151) 343 9883 E-Mail: hnl-bromborough@europe.heraeus.com

Internet: www.heraeus-noblelight.com

Printed in Germany · HNG - B 25 E · D 5C 08.00/M+T

BEG, NO. 39254

CE

Heraeus Amba Australia Pty. Ltd. Unit 3, 41-49 Norcal Road Nunawading, Victoria, 3131 Australia Phone +61 (3) 9874 7455

Telefax +61 (3) 9874 7488 E-Mail:

sales@heraeus-amba.com.au Internet: www.heraeus-amba.com.au

**TECHNICAL DATA** 

- medium wave, 1200 °C, peak wavelength 2 µm
- maximum power density 150 kW/m<sup>2</sup>

(carbon round tube 100 kW/m², medium wave twin tube 50 kW/m²)

- maximum linear power density 70 W/cm
- switch on and off times of only 1 or 2 seconds
- conventional mains voltages
- twin tube format 33 x 14 mm
- designs A B C D
- lengths up to 3 m
- gold plated
- one- or two-sided connection

# RANGE OF THE CARBON TWIN TUBE EMITTER

Model	Heated length [mm]	Voltage [V]	Power [W]	Max. linear power density [W/cm]	Maximum power density [kW/m²]
А	100 – 1500	Standard e.g.	350 – 5250	35	75
В	100 – 1500	115, 230	700 – 10500	70	150
С	100 – 1500	400, 480	700 – 10500	70	150
D	100 – 3000		350 – 10500	35	75

