

## Material-Datasheet

Product description

White Inkjet-, Laser-, and Copierlabels

<b>Face material</b>	
Material description	Matt white wood free paper with good opacity and standard characteristics.
Suitability	DIN A4 sheets suitable for all popular Inkjet desktop printer models, Colour/ monochrome laser printers and monochrome copiers
Thickness	77 ± 5 µm
Grammage	67 ± 5g/m <sup>2</sup>
<b>Adhesive</b>	
Type	Permanent, acrylic based adhesive
Performance	The adhesive features good tack and adhesion performance on a wide range of substrates, even at low temperatures. The adhesive complies with the European food regulations and regulations. It can be used for the labelling of food packaging .
<b>Liner</b>	
Type	One side coated, bleached kraft paper
Thickness	56 ± 6 µm
Grammage	56 ± 6g/m <sup>2</sup>
<b>Laminate</b>	
Grammage	140 ± 5 g/m <sup>2</sup>
Service temperature	Ca. -30 °C to +80 °C no negative influence with a short-time higher temperature e.g. during printing on a laser printer
Min. applicaton temperature	0 °C
Optimal storage conditions	approx. 23 °C room temperature and 50% of relative humidity
<b>Recycling</b>	
Surface material and liner	The liner is neutral and contains neither hazardous nor water pollution material. Small amounts can be added to the paper recycling process.

N.B.:All data to be considered as typical values