

NOTE

Thank you for your purchase of this CEC turntable with S-shaped tonearm. Because the owner's manual included id made specially for ST930 with straight tonearm, there are the following discrepancies against the owner's manual:

1. The attached stylus position gauge is marked H-50151-00.
2. No fixing screw for the main weight is supplied.

NOTE FOR MOUNTING A CARTRIDGE ONTO THE TONEARM

In case that the gross weight of your cartridge including mounting screws, nuts and so on goes out of the scope 4 - 9g for straight tonearm, or the scope 5 - 12g for S-shaped tonearm, using the supplied counterweight, you may not balance the tonearm to get proper stylus force or put the dust cover onto the unit. In such cases, refer to the following table to select and use a proper counterweight sold as an option.

Type of Tonearm	Gross Weight of Cartridge	Proper Counterweight
Straight	2 - 7g	CST-L
	4 - 9g	CST-M(supplied)
	9 - 18g	CST-H
S-shaped	2 - 6g	CSS-L
	5 - 12g	CSS-M(supplied)
	12 - 23g	CSS-H

For getting stylus force of 1.5g

NOTE FOR MOUNTING THE S-SHAPED TONEARM

Before mounting the S-shaped tonearm onto the unit, using the stylus position gauge H-50151-00, mount the cartridge into the tonearm in place. Then fix the tonearm so that the distance between the center of turntable shaft and the stylus is 224mm when the tonearm is held at the Tonearm Rest , as shown in the figure below.

