



TG3

HIGH PERFORMANCE PRINTER FOR THE RETAIL INDUSTRY

FEATURES

- /// Supports Tags up to 0.33 mm thick
- /// High Print Speed of 10 ips
- /// Large LCD Display
- /// Prints Brand Names and Logos
- /// Automated Print-Cut-Stack Function
- /// RFID Ready

APPLICATIONS

- /// Retail
- /// Product and Price Labelling
- /// Swing Ticket Labelling

PRINTING SPECIFICATION		TG308	TG312
Printing Method		Direct Thermal and Thermal Transfer	
Print Resolution, dots/mm (dpi)		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max. Print Area	Width, mm (inch)	80mm (3.15")	
	Length, mm (inch)	240mm (9.45")	
Print Speed, mm/sec (ips)		Up to 250mm/sec (10ips)	
CPU		32 bit RISC	
Printer Body Memory		Flash ROM: 8MB	

CONSUMABLES SPECIFICATION (Recommended to use printer supplies manufactured or certified by SATO)			
Sensor Type		I-Mark Sensor (Reflective), label Gap Sensor (Transmissive), side-hole sensor, notch sensor, jump-hole sensor	
Media Type		Roll die cut labels, Plain paper face stock, Synthetics, Continuous stock and Tags	
Media Thickness	Label	0.14 – 0.265mm (0.0055" – 0.01")	
	Tag	0.157 – 0.33mm (0.0061" – 0.013")	
Label Shape	Diameter	Max. outside diameter: Ø 254mm (10"), Core diameter: Ø 76.2mm (3") or Ø 101.6mm (4")	
	Wind Direction	Face-in	
Label Size	Continuous	Width	22 – 80mm (0.87" – 3.15")
		Length	16 – 237mm (0.63" – 9.33")
	Cutter	Width	22 – 80mm (0.87" – 3.15")
		Length	22 – 237mm (0.87" – 9.33")
Tag Size	Continuous	Width	32 – 83mm (1.26" – 3.27")
		Length	25 – 240mm (0.98" – 9.45")
	Cutter	Width	32 – 83mm (1.26" – 3.27")
		Length	25 – 240mm (0.98" – 9.45")
Ribbon	Size	Width: 39.5mm (1.56") to 84mm (3.31"), Max. Length: 450m (1476')	
	Core Diameter	Ø 25.4mm (1")	
	Wind Direction	Face-in/out	

FONTS / SYMBOLOGIES		
Fonts	Standard Fonts	Bitmap Fonts Alphanumerical and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)
	Rasterized Fonts	CG Times, CG Triumvirate
Barcode	1D Barcode	UPC-A/E, JAN/EAN-8/13, Code 39, Code 128, GS1-128 (UCC /EAN128), Codabar (NW-7), Interleaved 2 of 5, Bookland (2/5 char add-on code), GS1 Databar (RSS14), Composite JAN/EAN-8/13; Composite UPC A/E; Composite GS1 128/CC
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)
Print Rotation	Character Data / Barcode	0°, 90°, 180°, 270°

COMMUNICATION INTERFACE	
Optional Plug-in Interface	IEEE1284, Centronics parallel, RS232C (2400-19,200 Baud), RS232C highspeed (9,600-57,600 baud), USB (12Mbit/s), LAN (TCP/IP protocol 10/100BaseT), Wireless LAN 802.11b/g
Standard	External I/O Port, Serial Port for Keypad
Command	SBPL

OPERATING CHARACTERISTICS		
Power Requirements	Input voltage AC100-240V (auto switching)/132W (peak)	
Consumption Voltage	At Peak: 132W, On Standby: 20W	
Environment	Operating	5 – 40°C / 30 – 80% RH (without condensation)
	Storage	-5 – 60°C / 30 – 90% RH (without condensation)
Dimension	(W x D x H): 284 x 552 x 300mm (11.2" x 21.7" x 11.8")	
Weight	16.2 kg (35.7 lbs)	

MISCELLANEOUS	
Certifications	FCC, UL, KCC, CSA, CCC, CE, ROHS compliant

OPTIONS	
Accessories	Large Stacker, Label Rewinder, RFID Kit (UHF and HF), Ribbon Core Adaptor Kit, Keypad, Smart Keyboard, NiceLabel, Real-Time Clock

SATO makes no guarantee that the above features are available in all models, and specifications are liable to change, without notice. Version 09/10. * Measurements are approximate values.