CITIZEN

szybki wydruk paragonów, górne wyj?cie papieru

Us?ugi o najwy?szym standardzie



CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)

Applications

- Hospitality
- Kiosk
- Kitchen
- Retail



CITIZEN

Specifications

Model	CT-S851II
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	300 mm/sec.
Print Width (maximum)	45 / 48 / 52 / 54 / 64 / 68 / 72 / 80 mm
Media Width (min to max)	58 / 60 / 80 / 83 mm (+/- 1mm)
Roll Size (max), Core Size	83 mm outside diameter
Media Thickness (min to max)	65 to 75 ?m or 75 to 150 ?m or 85 to 150 ?m
Main Interface	None: interface card slot for optional card
Interface	Bluetooth with Apple™ MFi compatibility, Compact Wireless LAN, Premium Wireless LAN, Serial (RS-232C compliant), Parallel (IEEE 1284 compliant), USB, USB with hub, Powered USB, External device port, RJ-45, 8-pin connector
Power supply	100 - 240V, 50/60hz
Reliability	200 Million pulses or 150 Km, 2 million cuts
Emulations (Languages)	ESC/POS TM
Drivers and software	Free-of-charge from website, including support for various platforms
Cutter	Guillotine type, full and partial

CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)

Features & Benefits

- Low space requirement integrated power supply enables clean work station
- Mobile-POS ready
- Easy notification built-in buzzer
- ENERGY STAR® compliant
- Small footprint
- Recyclable packacking
- Tool-free maintenance



CITIZEN

Model CT-S851II

EMC and safety standards

CE, TUV, UL, C-UL, FCC class A

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

CT-S851II

POS, Receipt printer (thermal 3 inch / 80mm)