

NEAR FIELD / SHORT RANGE UHF ANTENNA - A1001

ABOUT TIMES-7

Pushing the boundaries of RFID technology worldwide Times-7 are leaders in RFID antenna design and manufacture. Our patented award winning UHF antennas meet the needs of virtually any industry application; providing customers with fast accurate tracking of products, assets & people; empowering organizations to transform processes & reduce costs.

Our SlimLine range of antennas is unique in the RFID industry; offering high levels of performance & durability in an aesthetically superior form.

Proven in a diverse & growing range of markets, applications include: retail & customer interaction, conference & people tracking, race timing, baggage handling, and logistic & supply chain asset management.



The A1001 Near Field Antenna

Wideband near field UHF RFID antenna

82 mm / 3.2" square footprint

Read distance: o to 10 cm / 3.4 in.

Typical applications:

Access control & security, retail POS,
libraries, & mass transit systems

Offering a breakthrough in size and performance the A1001 is a small commercially available wideband near field UHF RFID antenna.

Ideal for enclosed spaces and anywhere a small footprint is required, the A1001 Near Field / Short Range UHF antenna provides wideband reception and transmission of signals in the 864-928 MHz frequency range (ETSI & FCC bands inclusive).

The A1001 antenna offers impressive performance in a small footprint, greatly reducing stray tag-reads, and illustrates the advantage of near field / short range RFID in a truly cost-effective solution.

Specifications

Physical / Environmental Specifications

Dimensions (L x W x D):	82.0 mm x 82.0 mm x 9.5 mm	
	3.2 " x 3.2 " x 0.3 "	
Weight:	100 g / 0.22 lbs.	
Casing:	Moulded ABS housing	
Environmental Rating:	No rating	
Operating / Storage Temperature:	0° to +50°C / -30° to +60°C	
	+32° to +122°F / -22° to +140°F	
Connector type / position:	Type SMA Female / Side	





NEAR FIELD / SHORT RANGE UHF ANTENNA - A1001

OUR GLOBAL NETWORK
Constantly increasing market reach

and influence in the global RFID industry, Times-7's international support spans The Americas, Europe, and Asia Pacific regions through our distributor, authorized reseller and integrated solutions provider network.

Electrical Specifications

Frequency Range:	864-928 MHz	
VSWR:	1.4 typical	
Nominal Impedance:	50 Ω	
Maximum Input Power:	1 W	

Order Information

(please quote both product code & part no.)

(prease quote both product code a part no.)				
Product Code	Band	Part No.		
A1001	ETSI / FCC Wideband	71203		
Cable Accessories	Cable Type	Part No.		
Cable 2 m, SMA to RPTNC	195 / 240	71436 / 71782		
Cable 4 m, SMA to RPTNC	195 / 240	71437 / 71784		
Cable 6 m, SMA to RPTNC	LMR 240	71904		
Cable 8 m. SMA to RPTNC	195 / 240	71438 / 71788		

Applications

- Access Control & Security
- Retail POS
- Libraries
- Mass Transit Systems







The technical data contained in this publication is not a guarantee for which Times-7 Research Ltd assumes legal accountability. It is indicative of typical performance, and if required should be relied on for specific applications only after due verification.

All technical data, specifications and other information contained herein are deemed to be the proprietary intellectual property of Times-7 Research Ltd. No reproduction, copy or use thereof may be made without the express written consent of Times-7 Research Ltd.

info@atlasRFIDstore.com • www.atlasRFIDstore.com



