

DATASHEET EOS-100

EOS-100

The Tageos EOS-100 is a wide-band Gen2 UHF RFID label with a short read range designed for Jewelry tagging. The label is die-cut to provide three different label shapes suitable for tagging earrings, rings, necklaces and watches.



GENERAL SPECIFICATIONS

| Frequency | FCC 902–928 MHz / ETSI 865–868 MHz / ASIA 950–956 MHz |
|-------------|---|
| Protocol | EPC Class 1 Gen 2 |
| EPC memory | Up to 128 bits |
| User memory | Up to 128 bits |
| | |

Antenna size 14 x 11 mm / 0.55 x 0.43 in

Label size 100 x 26 mm / 3.94 x 1.02 in LABEL CONFIGURATIONS

11








Rings & Necklaces

MECHANICAL **DIMENSIONS**

| DIMENSIONS | DESCRIPTION | METRIC | US |
|------------|---------------------|----------------|----------------|
| A x B | Antenna size | 14 X 11 MM | 0.55 x 0.43 in |
| C x D | Die-cut size | 100 X 26 MM | 3.94 x 1.02 in |
| E | Web width | 106 mm | 4.17 in |
| F | Pitch | 30 mm ± 0,5 mm | 1.18 in |
| G | Die-cut to web edge | 3 mm | 0.12 in |
| HxI | Label size | 96 x 24 mm | 3.78 x 0.94 in |
| К | Bad mark | Ø4mm | Ø 0.62 in |



FEED DIRECTION _



DATASHEET EOS-100

rfid chip Silicon

| TAG SILICON | ALIEN HIGGS 4 | IMPINJ MONZA R6 | IMPINJ MONZA R6-P |
|-----------------------|-----------------------------------|-------------------------------|-------------------------------|
| Protocol | EPC Class 1 Gen 2 | EPC Class 1 Gen 2 | EPC Class 1 Gen 2 |
| Operating frequency | 860 - 960 MHz | 860 - 960 MHz | 860 - 960 MHz |
| EPC memory | Up to 128 bits | 96 bits | Up to 128 bits |
| User memory | 128 bits | - | Up to 64 bits |
| Operating temperature | -50°C / +85°C (-58°F / +185°F) | -40°C/+85°C (-40°F/+185°F) | -40°C/+85°C (-40°F/+185°F) |

PRODUCT CHARACTERISTICS

| | ADHESIVE LABEL |
|---------------------|---|
| Antenna material | Aluminum |
| Front face material | Glossy white TT printable coated paper |
| Back face material | - |
| Adhesive | Solvent-free permanent acrylic adhesive |
| Final inspection | 100% tested, defective tags marked |

DELIVERY CONDITIONS

| | ADHESIVE LABEL |
|------------------------|--------------------------|
| Packaging | Roll (single row) |
| Core inner diameter | 76 mm / 3 in |
| Roll outer diameter | 200 mm / 7.87 in |
| Unwinding direction | Labels on inside of roll |
| Standard roll size | 2500 pcs |
| Minimum order quantity | One roll |

CERTIFICATIONS & APPROVALS

| ्रीन् JEBRA | TOSHIBA | | |
|-------------|---------|---------|--|
|-------------|---------|---------|--|

CONTACT@TAGEOS.COM WWW.TAGEOS.COM TAGEOS HEADQUARTERS 515, RUE ALFRED NOBEL 34000 MONTPELLIER FRANCE TAGEOS NORTH AMERICA 609 SW 8TH STREET, SUITE 600 BENTONVILLE, AR 72712 USA

STORAGE & HANDLING PRECAUTIONS: Observe standard storage and handling practices to minimize Electro Static Discharge. Tageos reserves the right to change its products and services at any time without notice. As our products are used in circumstances beyond our control, we cannot be held liable for any damages caused through their use.

This is a general purpose product not designed or intended for any specific application. The pictures and illustrations found on this document are for illustration purposes only, and do not necessarily represent the exact products. Tageos is a registered trademark. All other trademarks are the property of their respective owners.

01/2016

Jpdated