

# 1128 **BLUETOOTH**<sup>®</sup> UHF RFID READER

## HIGH PERFORMANCE, **BLUETOOTH**<sup>®</sup> WIRELESS ENABLED UHF RFID READER



With 2D Imager Antenna option



RFID-only Antenna with Slimline Grip



Trigger Handle and 2D UHF antenna



Custom Mount for Datalogic Skorpio X3



Modular design



### Data Collection Performance Like No Other

The TSL<sup>®</sup> 1128 *Bluetooth*<sup>®</sup> UHF RFID reader provides new levels of RFID performance. With its R2000 core and range of interchangeable high performance antennas, the 1128 performs like no other reader giving the user the highest levels of flexibility currently available in today's market. Designed to read and write to EPC Class 1 Gen 2 (ISO18000-6C) tags, the 1128 can also be configured with class leading high performance 2D barcode data scanning to bring unparalleled data collection capabilities to any host it is connected to. The Motorola SE4500 engine incorporates fast-pulse illumination and fast sensor shutter speeds, delivering outstanding motion tolerance and class leading 1D and 2D data capture.

### Platform Independent UHF RFID Reader

Use existing *Bluetooth*<sup>®</sup> wireless technology enabled<sup>1</sup> host devices including Enterprise Handhelds, Consumer Phones, Touchscreen MP3 players, Tablets and PC's – the 1128 will bring high performance RFID and 2D scanning to all these devices running a wide range of Operating Systems. The 1128 *Bluetooth*<sup>®</sup> UHF RFID reader can also be tethered to a PC using a USB cable.

Extensive software support is available for a wide range of platforms including code samples, demonstration applications and source code.

### As Easy As ABC....

The new 1128 *Bluetooth*<sup>®</sup> UHF RFID reader incorporates TSL's unique ASCII protocol for faster and easier application development. This sophisticated parameterised ASCII protocol provides the developer a powerful set of commands that carry out multiple actions locally within the reader. This approach enables multiple tag operations executed using simple pre-configured ASCII commands which not only speeds integration of the reader into applications but also abstracts the developer from some of the complexities of the underlying Native API and ultimately results in un-paralleled levels of performance.

### A Configuration To Suit Your Application

The choice of host device is yours - from low cost touchscreen MP3 players through to fully featured Enterprise Handheld Terminals. The choice of ergonomic style includes a compact slimline grip through to a comfortable trigger handle for scan intensive RFID and 2D bar code data collection applications.

EPC data can be stored on an optional Micro SD memory card (up to 500 million transponder EPCs on a 32GB card - separate purchase from alternative supplier). This provides the ability to collect and log data even if USB or *Bluetooth*<sup>®</sup> communication channels are not available.

### Features:

#### High Performance *Bluetooth*<sup>®</sup> Multi-modal Data Capture

UHF RFID and 2D barcode data capture in one integrated *Bluetooth*<sup>®</sup> device.

#### Hardware Platform Independence

Operates with wide variety of *Bluetooth*<sup>®</sup> wireless technology enabled host devices including touchscreen MP3 players, phones, tablets, Enterprise Handhelds and PC's.

#### OS Independence

Operates with Android, iOS, Windows 10, 8, 7, Vista, XP, Windows Mobile, Windows CE, and Windows Phone.

#### Batch Data Collection

Removable high capacity Micro SD data card and real time clock for extended batch data collection independent of host connection.

#### Flexible Configuration

Unique interchangeable high performance antennas including optional 2D scanning and trigger handle with a range of device specific mounts for holding phones and MP3 players.

#### High Performance Barcode Scanning

Integrated Motorola SE4500 imaging engine provides class leading barcode scan performance via its unique patent pending fast pulse illumination which delivers outstanding motion tolerance and class leading 1D and 2D data capture

# 1128 SPECIFICATIONS

## Physical and Environmental Characteristics

Dimensions (LxWxH):	16.0 cm x 7.7 cm x 16.9 cm – Trigger handle 16.0 cm x 7.7 cm x 9.7 cm – Slimline grip
Weight:	380 g / 13.4 oz (including battery & trigger handle)
User input:	Trigger button
User feedback:	Speaker, vibration motor, LED
Power:	Removable, rechargeable 4.2 volt Lithium Polymer 2400 mAh battery pack, 8.9 watt hrs
Enclosure materials:	Polycarbonate

## Performance Characteristics

RFID engine:	TSL® custom module with embedded Impinj R2000
Communication protocols:	TSL® ASCII 2.0 parameterised command set Impinj binary
Memory:	Optional Micro SD card (maximum 32GB capacity supported). Up to 500 million date and time stamped EPCs can be stored on a 32GB Micro SD card (separate purchase from alternative supplier).
Compatible Host devices (Bluetooth®):	Any Bluetooth® Host <sup>1</sup> supporting the Serial Port Profile (SPP) or Human Interface Device (HID) profile (Android, iOS, Linux, Mac, Windows). See <a href="#">Bluetooth® Mode Comparison</a> .
Compatible Host devices (USB):	Any USB host with FTDI VCP driver support (Windows, Linux, Mac, Android)

## Environmental

Operating Temp.:	-10°C to 40°C (14°F to 104°F)
Charging Temp.:	5°C to 40°C (41°F to 104°F)
Storage Temp.:	Less than 1 month at -20°C to +45°C (-4°F to 113°F) Less than 6 months at -20°C to +35°C (-4°F to 95°F)
Humidity:	5% to 85% non-condensing
Drop Spec:	Multiple drops to concrete: 4 ft./1.2 m ambient, 3ft / 0.9m across the operating temperature range
Tumble:	500 0.5 metre tumbles at room temperature (1,000 cycles)
Environmental Sealing:	IP54
Electrostatic Discharge (ESD):	± 15kVdc air discharge; ± 8kVdc contact discharge
MIL-STD 810F:	Meets and exceeds applicable MIL-STD 810F for drop, tumble and sealing

## RFID Performance

Standards supported:	EPC Class 1 Gen 2
Nominal read range <sup>2</sup> :	Up to 7m (23ft)
Nominal write range <sup>2</sup> :	Up to 2m (6.5ft)
Field:	150-degree forward facing (approx.) measured from front of device
Antenna:	Detachable, Circularly Polarized with optional 2D scanner
Frequency Range:	EU: 865-868MHz; US: 902-928MHz

Maximum Output Power:	32dBm EIRP or maximum for regulatory region
Antenna options:	High Performance CP High Performance CP with 2D Imager Custom antennas available

## Barcode Scanning

Imager:	Motorola SE4500 2D imager																
Sensor Resolution:	752 x 480 pixels																
Field of View:	Horizontal: 40°, Vertical: 25°																
Focal Distance:	SR: 8 in. DL: 5.3 in. HD: 2.9 in.																
Aiming LED (VLD):	655 ±10 nm Laser																
Illumination:	625 ±5 nm LEDs (2x)																
Min. Print Contrast:	Minimum 25%																
Symbologies Supported:	1D: All major codes 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal (KIX)																
Ranges <sup>3</sup> :	<table border="1"> <thead> <tr> <th></th> <th>DL Focus</th> <th>Near</th> <th>Far</th> </tr> </thead> <tbody> <tr> <td>5 mil Code 39</td> <td></td> <td>1.4 in./36 mm</td> <td>7.3 in./185 mm</td> </tr> <tr> <td>100% UPC</td> <td></td> <td>1.6 in./41 mm</td> <td>12 in./305 mm</td> </tr> <tr> <td>5 mil PDF417</td> <td></td> <td>2.8 in./71 mm</td> <td>4.5 in./114 mm</td> </tr> </tbody> </table>		DL Focus	Near	Far	5 mil Code 39		1.4 in./36 mm	7.3 in./185 mm	100% UPC		1.6 in./41 mm	12 in./305 mm	5 mil PDF417		2.8 in./71 mm	4.5 in./114 mm
	DL Focus	Near	Far														
5 mil Code 39		1.4 in./36 mm	7.3 in./185 mm														
100% UPC		1.6 in./41 mm	12 in./305 mm														
5 mil PDF417		2.8 in./71 mm	4.5 in./114 mm														

## Communication

Bluetooth®:	Bluetooth® Version 2.1
Bluetooth® Profiles:	SPP Profile, HID Profile, Apple iAP
Bluetooth® Power:	Class 2
Bluetooth® Range <sup>4</sup> :	30m
Bluetooth® Pairing:	PIN, Simple Secure Pairing, NFC OOB Pairing

## Peripherals and Accessories

External interface:	MicroUSB connector for battery charging, and USB connectivity.
USB operating modes:	Tethered for real time data capture in conjunction with SmartWedge software. Download of stored scan data.
Optional charger:	TSL® 1136 4-Slot desktop charger
Other Accessories:	Adapter mounts are available for a variety of smartphones handheld terminals. Slimline Grip, Trigger Handle

## Regulatory

General:	Approved for use in the US, Canada, Europe, Australia, Brazil, China, Hong Kong, Japan, Malaysia, Singapore, South Korea, Taiwan, Thailand and UAE.
Electrical Safety:	Certified to UL60950-1, CSA C22.2 No. 60950-1, IEC 60950-1, EN 60950-1
EMI/RFI:	USA: FCC Part 15 Canada: ICES 003 Class B, RSS-Gen, RSS-102, RSS-247 EU: EN 301 489-3, EN 301 489-1, EN 301 489-17, EN 302-208, EN55022 Class B, EN55024
Laser Safety:	IEC Class2/FDA Class II in accordance with IEC60825-1/EN60825-1, 21CFR1040.10

# EXAMPLE CONFIGURATIONS



With Honeywell Dolphin D75e



With Apple iPod touch® (4th & 5th gen)



With Motorola ES400



With *Bluetooth*® wireless technology enabled computer



With Samsung Galaxy Tab S



With iPhone 6 Plus