
PTK DELTA DESIGNS, PRODUCES AND SUPPLIES TO ITS CLIENTS REINFORCING PROFILES FOR WINDOWS AND DOORS.

PTK DELTA is one of the biggest Russian producers of steel reinforcing profiles for plastic window and door frames. Over the last 15 years we have made it from a small factory to the leading manufacturer of the domestic market with 40 000 t of finished products annually.



Starting from 2017 we have been expanding our business into the Europe together with our official distributor SeverTex, registered in Latvia. We are glad to offer our European clients the high quality certified products and also the services, that will make the purchase easier. No more complicated logistics, tedious customs clearance. We will take care of it! High quality profiles from Russia are closer to you now. Average delivery time is only 14 days.

ABOUT MANUFACTURER



More than 200 profile shapes

PTK DELTA - 5000 sq. meters warehouse premise

100% finished product quality control

Delta has two sheet metal slitting machines with daily capacity of 250 t. The finished products are steel strips with thickness from 0.4 to 2,5 mm and width up to 1600 mm.

SIA SeverTex. Official distributor in EU
Riga, Rupniecibas iela 54, LV-1045
Tel: +371 27 122-872 (LV) +39 331 825-96-30 (IT)
prof@sever-tex.ru www.sever-tex.ru







































DELTA

STEEL REINFORCING PROFILES MANUFACTURING

REHAU
BRUSBOX
PROPLEX
EXPROF
KBE
GEALAN
VEKA
THYSSEN
MONTBLANC
LG
PLAFEN
ARTEC
ALUPLAST
WINTECH
SALAMANDER
SCHUCO
SLIDORS
BRUGMANN
TROCAL
DARWIN
GUTWERK

PRODUCT LIST

DELTA

NAME	SKETCH	NAME	SKETCH	NAME	SKETCH	NAME	SKETCH
REHAU 245536		KBE S806		GEALAN 8701 GEALAN 8751		DECEUNINCK NA-21	
REHAU 244506		KBE 318		GEALAN 8703 GEALAN 8753		ARTEC S11	
REHAU 244516		KBE 208		GEALAN 3728		ARTEC S12	
REHAU 264005		KBE 640		GEALAN 509		PLAFEN ME 60L/Z	
REHAU 268742		MONTBLANC MT-1		IVAPER 1702		PLAFEN ME 60T	
REHAU 215886 KBE 614		MONTBLANC MT-2		IVAPER 1703		VEKA 113025	
KBE 207		MONTBLANC MT-K		IVAPER 3727		VEKA 113.002	
KBE 203		MONTBLANC-ЭКО		IVAPER 28x28		VEKA 113.229	
KBE 337		LOGIC		U-profile 28x28		VEKA 113.229.1	
KBE 604		GEALAN 3705		DECEUNINCK AR-1		VEKA 113.292	
KBE 614.1		GEALAN 3702		DECEUNINCK AR-3		VEKA 113.023	
KBE 655		GEALAN 3710		DECEUNINCK NA-44		VEKA 113.024	
KBE 200		GEALAN 3723		DECEUNINCK NA-65		VEKA 113.010	
KBE 201		GEALAN 3725		DECEUNINCK NA-105		VEKA 113.306	

VEKA 113.060		GUTWERK S-791715		WINTECH 28x30		STREAMLINE 455 210	
VEKA 113.020		GUTWERK S-791715.1		SCHUCO 202 464		CT 2	
VEKA 113.147		GUTWERK S-793720		SCHUCO 202 610		BECKER ШВ. 35x27	
VEKA 113.149		BRUGMANN VS 102		SCHUCO 202 446		S 311.0.0.04.01 S-311	
VEKA 113.026 ALUPLAST 229001		BRUGMANN VS 302		SCHUCO 202623		PROPLEX PR 3220	
ALUPLAST 229101		WINTECH 102 01 28x25		SALAMANDER 215 025		U-profile 30x28	
ALUPLAST 229023		WINTECH 24x30		STREAMLINE 215 120		Hollow profile 28x40	

Steel reinforcing profile

Steel grade	DC01
Galvanized surface	Zn100-150
Steel wall thickness	0,7 – 2,5 mm
Standard length	6000 mm

Customized lengths upon request

Maximum Allowable Deviations

Nominal dimensions	0,5 mm
Length	5,0 mm
Parallel flanges	0,5 mm
Twist angle	2,0°
Camber	2,0 mm

We are producing anchoring base plates for doors and windows fastening.
Cold-forged from galvanized steel the plates are reliably resistant to the transverse loads and wind loads.

Mechanical Properties of steel acc. to EN 10130

Steel grade	Re max, n/mm2	Rm, n/mm2	A min, %
DC 01	280	270/410	28

Comparison table

Old	Old	Actual	Grade no.	Norm acc. Din/EN
St 12	Fe P01	Dc01	1.0330	10130/10131

Chemical composition % of steel DC01 (1.0330): EN 10130-2006

C	Mn	P	S
max 0,12	max 0,6	max 0,045	max 0,045