



8000
White



8001
Black



8002
Marigold



8003
Tangerine



8004
Scarlet



8005
Fir Green



8006
Spring Green



8007
Purple



8008
Powder Blue



8009
Riviera



8010
Sky Blue



8011
Etruscan Blue



8012
Sea Green



8013
Cream



8014
Arras Red



8015
Brown



8016
Dark Scarlet



8017
Grass Green



8018
Tan



8019
Steel Blue



8020
Silver Grey



8021
Ivory



8022
Apple Green



8023
Turquoise



8024
Lime Green



8025
Pink



8026
Lavender



8027
Jade

Please note every effort has been made to make the colours representative of actual product. However the colour reproduction method does not always allow for this. Variations in the firing process can result in a deviation to the colour achieved.



8100
Normal Flux



8101
Hard Flux



8102
Silver Flux



8103
Light Rose



8104
Ruby



8105
Amethyst



8106
Gold



8107
Bronze



8108
Autumn



8109
Crystal Blue



8110
Lt Sapphire



8111
Midnight



8112
Warm Grey



8113
Elf Green



8114
Celeste Green



8115
Mallard



8116
Turquoise



8117
Peridot Green



8118
Soft Flux



8119
Brown



8120
Blue Turquoise



8121
Sapphire



8122
Amber



8123
Pearl Grey



8124
Bronze



8125
Dove Grey



8126
Electric Blue



8127
Purple Grey



8128
Blue



8129
Royal Blue



8130
Yellow



8131
Grass Green



8132
Kingfisher



8133
Smokey Grey



8134
Paprika

Please note every effort has been made to make the colours representative of actual product. However the colour reproduction method does not always allow for this. Variations in the firing process can result in a deviation to the colour achieved.

LEAD FREE JEWELLERY ENAMEL

DATA

Transparent jewellery enamel

Firing temperature: 820°C - 840°C

Application: Enamel can be dusted or wet inlayed to gold, silver and copper. All gold bearing ruby's and pinks require 8100 flux applied during the first application on Silver. Flux can be used on copper to enhance the colour. Lump can be used to give a raised appearance to the enamel or for use in scrolling technique.

Grades: Transparent in powder – Standard is 60's mesh. However, 50's – 200's mesh or 60's – 200's mesh can be supplied on request which will entail a surcharge.

Opaque jewellery enamel

Firing temperature: 780°C – 800°C

Application: Enamel can be dusted or wet inlayed to gold, silver and copper. Lump can be used to give a raised appearance to the enamel or for use in scrolling technique.

Grades: Opaque in powder – Standard is 80's mesh.