



SOUDAFIX VE-400SF

: 23/09/15

: 1 2

20°C	(65%)*	10°C	90	24
		-5°C	90	14
		0°C	45	7
		5°C	25	2
		10°C	15	80
		20°C	6	45
		30°C	4	25
		35°C	2	20
		40°C	1,5	15
		1,77 / ³		
		-40°C +120°C		
		14.000 / ²		
		15 / ² (DIN 53504)		
		100 / ² (DIN 53504)		

SOUDAFIX VE-400SF – (280 380)

18 +5 °C

(-10°C) +25 °C

Class F120.

EPA- : -10°C +40 °C.

SOUDAFIX VE-400SF.

SOUDAFIX VE-400SF

: 23/09/15

: 2 2

d	M8	M10	M12	M16	M20	M24	M27	M30
D ₀	10	12	14	18	24	28	32	35
h _{ef,min}	60	60	70	80	90	96	108	120
h _{ef,max}	160	200	240	320	400	480	540	600
C _{min}	40	50	60	80	100	120	135	150
S _{min}	40	50	60	80	100	120	135	150
T _{inst}	10	20	40	80	120	160	180	200

d	Ø8	Ø10	Ø12	Ø14	Ø16	Ø20	Ø25	Ø28
D ₀	12	14	16	18	20	24	32	35
h _{ef,min}	60	60	70	75	80	90	100	112
h _{ef,max}	160	200	240	280	320	400	480	540
C _{min}	40	50	60	70	80	100	125	140
S _{min}	40	50	60	70	80	100	125	140