

**DESCRIPTION**

Patented PVC tight fibered cotton composite corner tape that is 2-1/4" wide, .016" thick and comes in 50', and 100' rolls. Strait-Flex MEDIUM has a recess running the length of tape, which makes folding quick and is adjustable to any angle. Material is very stable with temperature changes and is flexible while maintaining it's rigidity when wet.

**ADVANTAGES**

- Creates perfect inside 90° corners and angled corners.
- Inside angles of bay windows.
- Inside ceiling corners.
- Straightens minor framing irregularities.
- Two times stronger than paper tape.
- Twice as fast as paper or mesh tapes.
- Slightly thinner than Original.
- Slotted edges ensure superior bond.

**WARRANTY**

Strait-Flex products are backed by a lifetime warranty. When applied to a sound structure, built on a permanent foundation using recommended application techniques, we warrant that these products will not edge-crack for the lifetime of the structure. Not recommended where structural movement may occur. Contact Strait-Flex International Inc for complete details.

**DIRECTIONS**

- Cut Strait-Flex's MEDIUM to desired length and trim ends at 45-degree angles. Fold MEDIUM in half at center crease with print size facing each other. For inside corners, fold less than desired angle with print side facing out.
- Apply all-purpose compound to corner. Press MEDIUM into the wet compound, adjust to create a straight line, and wipe down with a taping knife. A second coat can be applied immediately. Let dry completely over several hours or overnight.
- With a 6" or 8" taping knife, apply your final coat of compound feathering the compound beyond previous coat. For inside corners, a very light coat of compound is all that's needed. Let dry completely over several hours or overnight.
- Sand lightly with 120 grit sandpaper. MEDIUM will not fuzz-up like paper or mesh tapes.

**STORAGE**

Store in dry place protected from moisture.

**SUBMITTAL APPROVALS**

\_\_\_\_\_  
JOB NAME

\_\_\_\_\_  
CONTRACTOR

\_\_\_\_\_  
DATE

