Article DE-WCV-WIFIDB010

## WIFI doorbell USER MANUAL

### (V1.0)

#### **Product Parameter**

Video Ffrequency	720p lens, angle: 125 degrees	
Infrared night vision	850	
Terminal System	IOS6.0+、Android 4.4+	
Voice Frequency	Digital Encoder technology	
Operating voltage	DC_12V	
Operating current	300MA	
Humidity	20%-85%	
Power supply mode	External power supply	

# \*Application Installation 2 WiFicAM.RU

Mobile terminal can find in the store iHD Bell, also can scan qr code, click on the downloaded application software for installation.





IOS

After installation, the main interface of the mobile will have the launch icon

\* Sketch map



Smart add:click	o start the ar



button "Add doorbell" for WIFI configuration The

*NOTE:* If you do not find the need to add the doorbell ID serial number, please click on the top right corner of the page

#### Three ways to connect WIFI



NOTE: If you do not find the need to add the doorbell ID serial number, please click on

the top right corner of the page ''refresh'' button

	Edit DoorBell	Done
Name	DoorBell5	
(ID	BRTD010402DT	PBE
(1) Username	a an	M
Password	≥ characters *	

The administrator's user name defaults to "Admin", the administrator default factory password is empty, click the button "Done", the configuration is successful and automatically enter the APP main interface.

	iHD Bell	Edit			
+ Add doo	orbell	0			
2. LAN c If you ar	DoorBell1 State: Offline BRTD010038GJXKY		PUBLI CLASSE ration, you can	C skip the 1	lstep
directly	click "skip" to Add DoorBe	search the	doorbell can be	added.	
Please con (I	figure the device in the cor ong press the call key 5 se	nfiguration mode conds)			
Input the cor equ	rrect WIFi password, is in ipment will be around ev	in the WIF	R PUBL	C	
SSID:	TANSA303	Refrection	ELEASE		
Password If you need t	Enter WiFi password Start configuration	onfigured network,			
	Next	)	Add DoorBell Bell 192.168.10.154	Search	C
	inually add	OR PU RELE			

#### 3、Manual mode:

Add bell in administrator authorization, you can manually add, manually enter the product ID and the administrator to add the user to set the user name and password, click finish, Wan and LAN can be completed.

<	Add Doorell				
Please con	figure the device in the config ong press the call key 5 seco	puration mode nds)			
Input the corequ	rect WIFi password, is in config ipment will be around even on t	uration mode of he WIFi			
SSID:	TANSA303	Refresh			
Password	Enter WiFi password	Show			
	Start onfiguration	RELI	ASE		
If you need t	Start onfiguration	Igured network,	Bells	Edit DoorBell	Done
If you need t	Start onfiguration	Igured network.	Bells	Edit DoorBell DoorBell2	Done
If you need t	Start onfiguration	Igured network,	Bells     Name     ID	Edit DoorBell DoorBell2 BRTD010325GC	Done
If you need t	Start onfiguration	Igured network	Bells  C Bells  C Bells  D Bells D Bells  D Bells  D Bells  D Bells  D Bells D Bells  D Bells  D Bells D Bells D Bells D Bells D Bells D Bells D Bells D Bells D Bell	Edit DoorBell DoorBell2 BRTD010325GC	Done
If you need t	Start onfiguration	RELE gured network, th_ FOR RE	Bells  C Bells  C Bells  D Name  D D  D  D  D  D  D  D  D  D  D  D  D	Edit DoorBell DoorBell2 BRTD010325GC	Done

At this point the device has been displayed online status, click on the online device to enter the monitoring interface, you can video dialogue, unlock, take pictures, video and monitor mode switching some of the operation.



p2pWiFicnm.ru

Call End

50Hz

**1. Monitoring mode:** There are three ways to choose (by clicking on the button in the upper left corner of the monitor screen to achieve), the default is "voice priority", can ensure smooth sound, the image to 10 frames per second speed refresh; the second is " Mode "can be based on the actual situation of the network automatically adjust the sound and image frame rate; the third is" 1080I "in the network speed and better conditions to ensure that the image to achieve the highest clarity and adjust the sound zero delay.

**2**、 **Frequency:** There are two settings mode, 50HZ and 60HZ, switching under different light sources can be achieved to eliminate the interference of video images to improve picture quality.

**3. Photo:** in the process of monitoring click on the "Photo" to take pictures and save in the phone storage

**4. Unlock:** In the monitoring state can be opened remotely to open the door lock operation, click on the "unlock" system will pop up the input password window, enter the password in the pop-up window to open the door lock, the system default password "123456 "

**5. Video:** in the monitoring state, click the "video" can be recorded and saved in the phone storage

6. Delay: Sets the time to extend the monitoring status

Bell

1080

Unioci

Hold to talk

**7. Hold to talk:** Press this button when the system is set to half-duplex mode. Do not let go of the call, do not press this button when full duplex.

8. Call End : Click this button to end the call and return to the main interface.



Страница 7 из 10

< Sys	tem setting	s Done
Tip: mobile client suppor	t echo cancellatio	n, but choose full d
Full duplex 1(At th	e same time the ir	ntercom to monitor)
Full duplex 2(Hold listening)	the microphone i	con to speak,Always
Voice prompts	on (	) off
Configuration mode	<ul> <li>on</li> </ul>	off
Hint language	<ul> <li>Chine</li> </ul>	se 💿 English
Monitor max. time(S)	300	
Conversation max. tin	ne(S) 60	P
Call wait max. time(S)	30	
Restart doorbell		>

1. Intercom mode: full-duplex 1 mode, you can talk with the monitor. Half-duplex 2 mode when you need to hold down the "Hold to talk" icon does not let go for intercom, monitor the state continues, do not hold the "Hold to talk" icon to speak when the other party will not hear the voice.

2, voice prompts: open the function of the doorbell will output voice prompts, turn off when no voice prompts.

3. Configuration mode: This feature can be opened directly into the configuration mode, when the shutdown can not be configured. For safety advice choose to turn off, this is also a safe mode.

- 4. Monitor max time: set the length of time to monitor the screen.
- 5. Conversation max time: set the length of the talk time.
- 6. Call waiting max time: set the length of the device call time.
- 7. Restart the doorbell: restart the doorbell.

#### (2) Administrator settings:

Click "Edit" to set the password, consisting of letters or numbers.



Click the "Add" button in the upper right corner to add a new user. After setting a new username and password, add the user name, password, and device ID serial number to other members to add the doorbell manually. You can add 8 users at the same time. All users will receive push messages if they have a doorbell or when the alarm is activated. In the admin settings menu, you can find out which user is monitoring.

Note: When a push message is received, the notification of the other members will be stopped if one of the users is connected



You can set the alarm state of the opening and closing and alarm trigger time and sensitivity.

#### (4) Equipment time settings:

The time and time zone of the device can be set and calibrated.

#### (5) Push settings:

••∞∞ 中国移动  奈 <b>く</b> DoorBell1	<sup>10:21</sup> Push settings	
Push Service	F	DR PU
Open this funct		RELE

close will not receive push messages.

#### (6) WIFI settings:

Connect different WIFI router devices.

#### (7) Lock settings:



Set the lock to open the time and set the unlock password, the initial unlock password

