

## TD 202 Specification

<b>Turntable section</b>	
Drive System	Belt Drive
Motor	DC Motor
Speed	33 1/3 RPM, 45 RPM
Rotation Speed Variation	+/-2%
Wow and Flutter	0.2%
Signal-to-Noise Ratio	67dB or higher (A-weighted, 20kHz LPF) 60dB or higher (unweighted, 20kHz LPF)
Platter	Aluminum Die-cast
Diameter of Platter	12", 300mm
<b>Tonearm section</b>	
	Alumi tube
Type	Static Balance, Straight
Effective Arm Length	8.8", 223.6mm
Stylus Pressure Range	0 to 4g
Supported Cartridge Weight	3.5 to 6.0g
Overhang	18.6mm
Anti-skating Adjustment	Supported
<b>Cartridge section</b>	
Type	MM type (Audio-Technica AT-95E)
Stylus Construction	Bonded Diamond
Frequency Response	20Hz to 20kHz
Channel Separation	>18dB
Channel Balance	2.5dB
Vertical Tracking Angle	20 degrees
Supported Load Impedance	47k ohms
Output Voltage	2.5mV (1kHz, 3.54cm/sec.)
Stylus Pressure	2.0g +/-0.5g
Cartridge Weight	5.7g +/-0.5g
Head-shell Weight	11g (including Screws, Nuts and Wires)

<b>Analog Output</b>	
Connector	RCA Pin jack (Gold-plated)
<b>Power</b>	AC 100 to 240V, 50/60Hz
<b>Power Consumption</b>	1.5W (less than 0.5W at Standby)
<b>Overall Dimensions (W x H x D)</b>	420 x 355x 121mm
<b>Weight</b>	Approx. 3.9 kg