



Factory Add.: Mingcun Town, Pingdu City, Qingdao, China
Office Add.: Floor 9, No. 29 Capital International Center,
No. 6 Changcheng South Road,
Chengyang District, Qingdao, China

Tel.: +86 532 85831197
Fax: +86 532 85831187
Website: www.qihangtyre.com
Email: info@qihangtyre.com.cn



EN



CN

QINGDAO QIHANG TYRE CO., LTD

ATV/UTV TYRE



KNIGHT



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x11-10	6	9.0	24.8	10.8	455	7
23x8-11	6	6.5	23.5	7.5	290	7
24x9-11	6	7.5	24.3	9.1	365	7
25x8-12	6	6.5	25.0	8.0	340	7
25x10-12	6	8.0	25.0	9.6	420	7
25x11-12	6	9.0	24.8	10.7	455	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	10.0	480	7
26x12-12	6	8.0	26.0	10.0	520	7
27x9-12	6	7.0	27.0	9.0	440	7
27x11-12	6	7.0	26.9	10.7	495	7
27x12-12	6	9.5	27.0	10.0	550	7
26x9-14	6	7.0	26.0	9.0	395	7
26x11-14	6	8.0	26.0	9.7	465	7



ATLAS



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x8-12	6	6.5	25.2	8.3	340	7
25x10-12	6	8.0	24.4	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	10.0	480	7
26x8-14	6	6.5	26.0	8.0	355	7
26x10-14	6	8.0	26.0	10.0	430	7
26x9-14	6	7.0	26.0	9.0	395	7
26x11-14	6	9.0	26.0	11.0	465	7
27x9-14	6	7.0	27.0	9.0	410	7
27x11-14	6	9.0	27.0	11.0	480	7
29x9-14	6	7.0	29.0	9.0	495	7
29x11-14	6	9.0	29.0	11.0	520	7

ATV/UTV TYRE




MARS-A



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
22x11-8	6	9.0	22.3	10.9	395	7
22x10-9	6	8.0	22.0	10.0	365	7
25x12-9	6	9.5	25.2	11.6	495	7
22x11-10	6	9.0	22.2	10.7	385	7
22x8-10	6	7.0	21.9	8.0	275	7
23x8-10	6	6.5	23.4	8.3	300	7
23x10-10	6	8.0	23.4	10.2	375	7
25x12-10	6	9.5	25.0	12.0	495	7
22x7-11	6	9.0	22.0	6.9	395	7
22x11-9	6	9.0	22.0	11.0	395	7
23x8-11	6	6.5	23.4	7.6	290	7
24x8-11	6	6.5	24.0	8.1	320	7
25x8-11	6	6.5	25.1	8.1	355	7
25x10-11	6	8.0	25.2	10.0	430	7
25x8-12	6	6.5	25.2	8.3	340	7
25x10-12	6	8.0	24.4	9.9	420	7
25x12-12	6	9.5	25.0	12.0	480	7
26x9-12	6	7.0	26.0	9.0	410	7
26x10-12	6	8.0	25.9	9.0	440	7
26x11-12	6	9.0	25.8	10.0	480	7
26x12-12	6	9.5	25.9	11.4	520	7
27x10-12	6	8.0	26.9	9.0	490	7
27x12-12	6	9.5	26.9	11.4	550	7
28x10-12	6	8.0	27.8	9.0	450	7

MARS-B



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x12-10	6	9.5	24.8	11.7	495	7
24x11-10	6	9.0	24.0	11.1	440	7
24x9-11	6	7.0	23.8	8.6	365	7
24x10-11	6	8.0	24.2	10.1	395	7
24x8-12	6	6.5	24.5	8.0	310	7
25x8-12	6	6.5	25.2	8.3	340	7
25x10-12	6	8.0	24.4	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	10.0	480	7
27x9-12	6	7.0	27.7	8.5	440	7
27x11-12	6	9.0	27.8	10.6	495	7

ATV/UTV TYRE




VICTORY



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x8-12	6	6.5	24.8	8.0	340	7
25x10-12	6	8.0	25.0	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	11.0	480	7
26x9-14	6	7.0	26.0	9.0	395	7
26x11-14	6	9.0	26.0	11.0	465	7
27x9-14	6	7.0	27.0	9.0	410	7
27x11-14	6	9.0	27.0	10.8	480	7
28x10-14	6	8.0	28.0	10.0	480	7
29x9-14	6	7.0	29.0	9.0	495	7
29x11-14	6	9.0	29.0	11.0	520	7
30x10-14	8	8.0	30.0	10.0	970	14



VENUS



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
23x11-10	6	9.0	23.0	11.0	440	7
24x9-10	6	7.0	24.0	9.0	365	7
24x11-10	6	9.0	24.0	11.0	440	7

ATV/UTV TYRE




VULCAN



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x8-12	6	6.5	24.8	8.0	340	7
25x10-12	6	8.0	25.0	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	11.0	480	7
27x9-12	6	7.0	27.0	9.0	440	7
27x11-12	6	9.0	26.9	10.7	495	7
28x9-12	6	7.0	27.8	8.8	440	7
28x11-12	6	9.0	27.8	10.8	520	7
27x9-14	6	7.0	27.0	9.0	410	7
27x11-14	6	9.0	27.0	11.0	480	7
28x9-14	6	7.0	27.8	8.8	440	7
28x11-14	6	9.0	27.8	10.8	520	7
30x9-14	8	7.0	29.9	8.8	905	14
30x11-14	8	9.0	29.9	10.7	1045	14
32x10-14	8	8.0	31.7	9.5	1105	14

APOLLO



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
24x11-10	6	9.0	24.0	11.1	440	7
24x9-11	6	7.0	24.0	8.9	365	7
24x10-11	6	8.0	24.2	10.1	395	7
24x8-12	6	6.5	24.5	8.0	310	7
25x8-12	6	6.5	25.2	8.3	340	7
25x10-12	6	9.5	25.0	11.0	610	7
25x12.5-11	6	9.5	25.0	12.0	610	7
25x12.5-12	6	8.0	24.4	9.9	420	7
26x9-12	6	7.0	26.0	9.0	410	7
26x11-12	6	9.0	25.8	10.0	480	7

ATV/UTV TYRE




ARES




Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
16x8-7	4	6.5	15.8	7.8	157	5
16x8-7	6	6.5	15.8	7.8	180	7
19x7-8	4	5.5	18.7	6.8	200	5
19x7-8	6	5.5	18.7	6.8	240	7
22x11-8	4	9.0	21.8	10.7	340	5
22x11-8	6	9.0	21.8	10.7	395	7

CETO




Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
145/70-6	6	4.5	14.0	5.7	185	7

EOS



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
21x7-10	6	5.5	20.6	6.6	235	7
20x10-9	6	8.0	19.9	9.9	300	7
22x7-10	6	5.5	21.4	6.7	255	7
23x7-10	6	5.5	23.0	7.0	275	7
22x10-10	6	8.0	21.7	9.9	355	7

EOS-H



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
20x11-9	6	9.0	20.0	11.0	340	7
22x11-9	6	9.0	22.0	11.2	395	7

ATV/UTV TYRE



OCEANUS



TETHYS

OCEANUS



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x8-12	6	6.5	25.0	8.3	340	7
25x10-12	6	8.0	25.0	9.4	420	7

TETHYS



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
22x10-9	6	8.0	21.9	10.0	365	7
22x7-11	6	5.5	21.9	7.1	245	7
25x8-12	6	6.5	24.8	8.1	340	7
25x10-12	6	8.0	24.9	9.8	420	7



MAXX PLUS




Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
24x11-10	6	9.0	24.0	11.1	440	7
24x9-11	6	7.0	23.8	8.6	365	7
24x10-11	6	8.0	24.2	10.1	395	7
24x8-12	6	6.5	24.5	8.0	310	7
25x8-12	6	6.5	24.8	7.9	340	7
25x10-12	6	8.0	25.0	9.8	420	7
26x9-12	6	7.0	26.0	8.9	410	7
26x11-12	6	9.0	25.8	10.8	480	7
27x9-12	6	7.0	27.7	8.5	440	7
27x10-12	6	8.0	27.0	10.0	505	7
27x11-12	6	9.0	27.8	10.6	495	7
27x12-12	6	9.5	27.8	10.6	550	7
27x9-14	6	7.0	27.7	8.5	410	7
27x11-14	6	9.0	27.8	10.6	480	7

ATV/UTV TYRE



RHEA



Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
25x8-12	6	6.5	25.2	8.2	340	7
25x10-12	6	8.0	25.2	9.5	420	7
26x9-12	6	7.0	25.7	8.8	410	7
26x11-12	6	9.0	25.8	10.0	480	7
27x9-12	6	7.0	27.7	8.5	440	7
27x11-12	6	9.0	27.8	10.6	495	7
26x9-14	6	7.0	26.0	8.5	395	7
26x11-14	6	9.0	26.0	9.7	465	7
27x9-14	6	7.0	26.0	8.5	410	7
27x11-14	6	9.0	26.0	10.0	480	7



RADIAL ATV TYRE

Size	PR	Max Load (Lbs)	Load/Speed Index	PSI	Available Pattern
25x12R10	6	495	56J	7	MARS-B
25x12.5R11	6	610	64J	7	APOLLO
25x8R12	6	340	43J	7	KNIGHT / MARS-A / MARS-B / TETHYS / OCEANUS / VICTORY / VULCAN/ MAXX PLUS / APOLLO
25x10R12	6	420	50J	7	KNIGHT / MARS-A / MARS-B / TETHYS / OCEANUS / VICTORY / VULCAN/ MAXX PLUS / APOLLO
25x12.5R12	6	610	64J	7	APOLLO
26x9R12	6	410	49J	7	KNIGHT / MARS-A / MARS-B / RHEA / OCEANUS / VICTORY / VULCAN/ MAXX PLUS
26x11R12	6	480	55J	7	KNIGHT / MARS-A / MARS-B / RHEA / OCEANUS / VICTORY / VULCAN/ MAXX PLUS
26x12R12	6	520	58J	7	KNIGHT/OCEANUS
27x9R12	6	440	52J	7	MARS-B / VULCAN / MAXX PLUS
27x11R12	6	495	56J	7	MARS-B / VULCAN / MAXX PLUS
26x8R14	6	355	44J	7	ATLAS
26x10R14	6	430	51J	7	ATLAS
26x9R14	6	395	48J	7	KNIGHT / ATLAS / VICTORY / OCEANUS
26x11R14	6	465	54J	7	KNIGHT / ATLAS / VICTORY / OCEANUS
27x9R14	6	410	49J	7	ATLAS / VICTORY / VULCAN / / OCEANUS / MAXX PLUS
27x11R14	6	480	55J	7	ATLAS / VICTORY / VULCAN / / OCEANUS / MAXX PLUS
28x10R14	6	480	55J	7	VICTORY
29x9R14	6	495	56J	7	ATLAS / VICTORY
29x11R14	6	520	58J	7	ATLAS / VICTORY
30x10R14	8	970	79J	14	VICTORY



OUTDOOR POWER EQUIPMENT



LG01

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
11x4.00-5	4	3.00	11.3	4.1	330	46
13x5.00-6	4	3.50	13.0	4.3	440	40
13x6.50-6	4	4.50	13.0	6.3	460	28
15x6.00-6	4	4.50	14.9	6.2	570	30
16x6.50-8	4	5.38	15.9	6.6	620	28
18x6.50-8	4	5.38	17.6	6.9	770	28
20x8.00-8	4	7.00	19.4	8.6	950	22

OUTDOOR POWER EQUIPMENT



LG02



LG03

LG02

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
18x8.50-8	4	7.00	17.7	8.0	815	22
18x9.50-8	4	7.00	17.7	8.7	1040	24
20x10.00-8	4	7.00	19.5	9.1	1190	22

LG03

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
18x8.50-8	4	7.00	18.0	8.5	815	22
18x8.50-8	6	7.00	18.0	8.5	1000	32



LG04

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
11x4.00-5	4	3.00	11.3	4.2	330	46
13x5.00-6	4	3.50	12.9	4.6	440	40
13x6.50-6	4	4.50	13.2	6.4	460	28
15x6.00-6	4	4.50	14.4	5.9	570	30
16x6.50-8	6	5.38	16.0	6.9	720	36
18x8.50-8	4	7.00	17.8	8.2	815	22

OUTDOOR POWER EQUIPMENT



GF01

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
22x11.00-10	4	9.00	23.0	10.0	1000	20
23x10.50-12	4	8.50	22.7	10.4	1000	20

GF02

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
205/50-10	4	6.00	18.1	7.8	675	30
215/40-12	4	7.00	18.9	8.0	760	30



GF01



GF02

OUTDOOR POWER EQUIPMENT



GF03



GF04

GF03

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
22x11.00-10	4	9.00	22.1	10.3	1000	20
23x10.50-12	4	8.50	23.2	9.7	1000	20

GF04

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
205/50-10	4	6.00	18.1	7.8	675	30
205/65-10	4	7.00	20.0	8.3	910	30
215/50-12	4	7.00	20.6	8.4	910	35
225/35-12	4	7.00	19.3	8.0	760	30
22x11.00-10	4	9.00	22.5	10.2	1000	20
23x10.50-12	4	8.50	22.7	10.4	1000	20



WAVE

Size	PR	Rim Width (Inch)	O.D. (Inch)	S.W. (Inch)	Max Load (Lbs)	PSI
11x4.00-5	4	3.00	11.3	4.1	330	46
13x5.00-6	4	3.50	13.0	4.3	440	40
13x6.50-6	4	4.50	13.0	6.3	460	28
15x6.00-6	4	4.50	14.9	6.2	570	30
16x6.50-8	4	5.38	15.9	6.6	620	28
16x7.50-8	4	5.38	16.1	7.2	680	24
18x6.50-8	4	5.38	17.6	6.9	770	28
18x8.50-8	4	7.00	17.7	8.0	815	22
18x9.50-8	4	7.00	17.7	8.7	1040	24
20x8.00-8	4	7.00	19.4	8.6	950	22
20x10.00-8	4	7.00	19.5	9.1	1190	22
20x8.00-10	4	7.00	19.8	8.1	895	24
23x8.50-12	4	7.00	22.4	8.5	1120	22
23x10.50-12	4	8.50	22.8	10.2	1340	20