SELF PRIMING CENTRIFUGAL PUMP

- ■SELF-PRIMING PUMP requires no water for subsequent pumping operation once initial pumping is done, and the pumping capacity is large.
- ■EFFICIENT, ECONOMICAL OPERATION is assured by directly coupled pump. It provides compactness and guarantees that power is not lost.
- ■WATER-RESISTING QUALITIES are prominent by adopting mechanical seal and the impellers which are made of special cast iron.
- ■HIGHLY ADVANCED ROBIN GASOLINE ENGINE, which is powerful and durable ensures easy maintenance and trouble-free operation.

DIESEL ENGINE PUMP

Model PTD306/PTD406/PTD405





PERFORMANCE CURVE 160 (ft) 140 40 120 Total Head 30 PTD406 PTD405 40 10 20 PTD306 500 1,000 1,500 2,000 100 200 300 400 500 600 Pumping Capacity (U.S. gal / min)

STANDARD ACCESSORIES



The left picture shows typical samples. Material and design may vary by models.

Available for PTD405




KEROSENE ENGINE PUMP

Model PTK206/PTK306



PERFORMANCE CURVE



STANDARD ACCESSORIES



The above picture shows typical samples. Material and design may vary by models.

SPECIFICATIONS

Model			PTD306	PTD406	PTD405
PUMP	Туре		Self-priming, Centrifugal pump		
	Suction×Delivery Diameters		76.2×76.2mm(3×3in.)	101.6×101.6mm(4×4in.)	101.6×101.6mm(4×4in.)
	Total Head		28m	27m	24m
	Maximum Delivery Volume		900 Ø/min	1300 Q/min	1800 @/min
	Suction Head		8m		
	Axle Seal Material(Mechanical Seal)		Ceramic-carbon		
	Model		DY23-2D	DY27-2D	DY35D
빌	Туре		Robin Air-cooled, 4-stroke, Diesel engine		
ENGINE	Fuel		Diesel light oil		
N.	Fuel Tank Capacity		3.2L		4.5L
	Starting System		Recoil starter		Hand cranking (Recoil starter as option)
	Dimensions (L×W×H) Net Weight		590×410×510mm	680×410×590mm	685×485×592mm
			43.5kg	52.2kg	69.6kg
	Standa	rd Accessories	Engine tool kit (1 set), Strainer (1 pc.), Hose coupling (2 pcs.), Hose band (3 pcs.)		
Wi	ith Wheel	Dimensions (L×W×H)	1		970×685×720mm
Kit	t & Stand	Net Weight	<u>-</u>		76.6kg

PTK206	PTK306			
Self-priming, Co	entrifugal pump			
50.8×50.8mm(2×2in.)	76.2×76.2mm(3×3in.)			
23	3m			
520 Q/min	800 Q/min			
8m				
Ceramic-carbon				
EY15-3DK	EY20-3DK			
Robin Air-cooled, 4-str	roke, Kerosene engine			
Kerosene (Automobile gasoline for starting)				
Kerosene 2.6L Gasoline 0.13L	Kerosene 3.4L Gasoline 0.17L			
Recoil starter				
470×355×419mm	527×379×422mm			
24kg	27.5kg			
Engine tool kit (1 set), Strainer (1 pc.), Hose coupling (2 pcs.), Hose band (3 pcs.)				
_				