



## Series 90\*-30 PLCs

GE Intelligent Platforms' Series 90\*-30 PLCs is a family of controllers, I/O systems and specialty modules designed to meet the demand for versatile industrial solutions — helping businesses gain a sustainable advantage. With its single overall control architecture, the Series 90-30 has been the PLC of record in over 200,000 applications such as high-speed packaging, material handling, complex motion control, water treatment, continuous emissions monitoring, mining, food processing, elevator control, injection molding and many more.

### **Its modular design offers unique versatility.**

Configure just the system you need, saving critical space and reducing cost. With over 100 I/O modules, the Series 90-30 PLC can be adapted to a wide range of applications.

- Digital interfaces for push buttons, switches, proximity sensors, relays, contactors and many other devices
- Analog modules with varying degrees of resolution for flow, temperature or pressure applications
- Direct connect wiring or remote termination
- Local or remote I/O systems

### **Ethernet communications provide a real-time link between the plant floor and the boardroom.**

You can begin with an Ethernet-enabled CPU, or at a later date, choose from our selection of rack-mounted Ethernet modules. The Series 90-30 Ethernet module supports both SRTP and Modbus TCP/IP application protocols.

### **The scalable processing power of the CPU creates a clear upgrade path.**

Create the system that's ideal today, while leaving open the option of creating a more powerful system tomorrow — without having to change your application software.

### **Integrated motion control fosters high performance, point-to-point applications.**

A variety of Series 90-30 field bus interfaces enables distributed control and/or I/O. Choose from Ethernet EGD, Profibus-DP™, Genius\*, DeviceNet™ and Interbus-S™ modules. Field Bus interface modules are easy to install and quick to configure. Plug them into an existing system or design a new system around them.

### **Programming is easy with Proficy\* Machine Edition.**

With the most advanced PLC programming tools on the market today, Proficy Machine Edition is an integrated solution for PLC and remote I/O hardware configuration, PLC programming languages, application development, and on-line diagnostics. Supported programming languages include Ladder Diagram (LD), Instruction List (IL), Structural Text (ST), and C Block.

### **The Series 90-30 stands out among small controls for offering redundancy options.**

The Series 90-30 is the low-cost solution for high availability applications, with redundant CPUs and power supplies.



# Series 90\*-30 PLCs

## Ordering Information

	Catalog Number	Description	Catalog Number	Description	
Discrete Input Modules	IC693MDL230	120 VAC Isolated Input (8 Points)	IC693MDL645	24 VDC Input, Neg/Pos Logic (16 Points)	
	IC693MDL231	240 VAC Isolated Input (8 Points)	IC693MDL646	24 VDC Input, Neg/Pos Logic, 1 msec Filter (16 Points)	
	IC693MDL240	120 VAC Input (16 Points)	IC693MDL648	48 VDC Input, Neg/Pos Logic, 1 msec filter, Neg/Pos Logic (16 Points)	
	IC693MDL241	24 VAC/VDC Input (16 Points)	IC693MDL654	5/12 VDC (TTL) Input, Neg/Pos Logic, (32 Points)	
	IC693MDL250 <sup>†</sup>	120 VAC Isolated Input (16 Points)	IC693MDL655	24 VDC Input, Neg/Pos Logic, 1 ms, (32 Points)	
	IC693MDL260 <sup>†</sup>	120 VAC Input (32 Points)	IC693MDL660 <sup>†</sup>	24 VDC Input, Neg/Pos Logic, 0.5ms, 1.0ms, 2.0ms, 5ms, 10ms, 50ms and 100ms filtering, (32 Points)	
	IC693MDL632	125 VDC Input (8 Points)	IC693ACC300	Input Simulator Module (8 Points)	
	IC693MDL634	24 VDC Input, Neg/Pos Logic (8 Points)			
Discrete Output Modules	IC693MDL310	120 VAC Output, 0.5 Amp (12 Points)	IC693MDL734	125 VDC Output, (6 Points)	
	IC693MDL330	120/240 VAC Output, 1 Amp (8 Points)	IC693MDL740	12/24 VDC Output, 0.5 Amp, Positive Logic (16 Points)	
	IC693MDL340	120 VAC Output, 0.5 Amp (16 Points)	IC693MDL741	12/24 VDC Output, 0.5 Amp, Negative Logic (16 Points)	
	IC693MDL350 <sup>†</sup>	120 VAC Isolated Output, 2 Amp (16 Points)	IC693MDL742	12/24 VDC Output, 1 Amp, Positive Logic (16 Points), Fused	
	IC693MDL390	120/240 VAC Isolated Output, 2 Amp (5 Points)	IC693MDL748	48/24 VDC Output, 0.5 Amps, Positive Logic (8 Points)	
	IC693MDL730	12/24 VDC Output, 2 Amp, Positive Logic (8 Points)	IC693MDL752	5/24 VDC (TTL) Output, Negative Logic, (32 Points)	
	IC693MDL731	12/24 VDC Output, 2 Amp, Negative Logic (8 Points)	IC693MDL753	12/24 VDC Output, Positive Logic (32 Points)	
	IC693MDL732	12/24 VDC Output, 0.5 Amp, Positive Logic (8 Points)	IC693MDL754 <sup>†</sup>	12/24 VDC Output, 0.75 amps, Pos Logic with ESCP protection, (32 Points).	
	IC693MDL733	12/24 VDC Output, 0.5 Amp, Negative Logic (8 Points)			
	Relay Output Modules	IC693MDL930 <sup>†</sup>	Relay Output, Isolated, 4 Amp (8 Points)	IC693MDL940	Relay Output, 2 Amp (16 Points)
		IC693MDL931	Relay Output, 8 Amp Form B/C contacts, Isolated in 2 Groups of 4 (8 Points)	IC693MDL916	Relay Output, 4 Amp (16 Points)
Mixed Discrete Modules	IC693MDR390	Mixed I/O, 24 VDC Input (8 points), Relay Output (8 points)	IC693MAR590	Mixed I/O, 120 VAC Input (8 Points), Relay Output (8 Points)	
Analog Input Modules	IC693ALG220	Analog Input, Voltage/Current, 4 Channels	IC693ALG222	Analog Input, Voltage 16 Single/8 Differential Channels	
	IC693ALG221	Analog Input, Current, 4 Channels	IC693ALG223	Analog Input, Current, 16 Single Channels	
Analog Output Modules	IC693ALG390	Analog Output, Voltage, 2 Channels	IC693ALG392	High Density Analog Output (8 Channels)	
	IC693ALG391	Analog Output, Current, 2 Channels			
Mixed Analog Modules	IC693ALG442	Analog Combo Module 4IN/2OUT			
Motion Modules	IC693APU300	High Speed Counter (HSC)	IC693DSM302	Digital Servo Motion Controller, 2 Axis	
	IC693APU301	Axis Positioning Module (APM), 1 Axis	IC693DSM314	Digital Servo Motion Controller, 1-2 Axis of Digital Servo or 1-4 Axis Analog Servo	
	IC693APU302	Axis Positioning Module (APM), 2 Axis	IC693DSM324	Digital Servo Motion Controller, 4 Axis of Digital Servo with fiber optic interface to amplifiers	
	IC693APU305	High Speed Counter with Gray Code Encoder or an A QUAD B Encoder Input			
Specialty Modules	IC693MDL760	Solenoid Valve Output (11 Points)/24 VDC Output, 0.5 Amp, Positive Logic (5 Points)	IC693PTM101	Power Transducer Module, CT and PT Interface 120/240 VAC (1m cable)	
	IC693PCM301	Programmable Coprocessor Module, 192 KB (47 KB Basic or C Program), 2 Serial Ports	IC693TCM302	Temperature Control Module, (8) TC In and (8) 24 VDC Solid State Outputs	
	IC693PCM311	Programmable Coprocessor Module, 640 KB (640 KB Basic or C Program), 2 Serial Ports	IC693TCM303	Temperature Control Module Extended Temperature Range, (8) TC In and (8) 24 VDC Solid State Outputs	
Communications Modules	IC693BEM331	Genius Bus Controller (Supports I/O and Datagrams)	IC693PBM200	Profibus DP Master Module	
	IC693CMM302	Communication Module, Genius (1 Kbyte) GCM+ (No Datagram Support)	IC693PBS201	Profibus DP Slave Module	
	IC693CMM311	Communications Module, CCM, RTU, SNP, and SNPx Protocols	IC693DNM200	DeviceNet Master Module	
	IC693CMM321	Ethernet Interface TCP/IP Module, 10Mbps (Supports SRTP and Modbus TCP/IP, No EGD)	IC693DNS201	DeviceNet Slave Module	
Remote I/O	IC693NIU004	Ethernet Network Interface Unit. Two Ethernet ports, one connection (one IP) with built in switch. Requires IC693CHS397 (5 slot rack) or IC693CHS391 (10 slot rack) and a Series 90-30 high capacity power supply.			
Controllers	IC693CPU311	5-Slot Base with CPU in Base (6KBytes User Program), Not Expandable	IC693CPU366	CPU 366 Module (240KBytes Configurable User Memory), with built-in Profibus Master (V1) Port, no built-in serial ports, Logic Execution is .22msec/K	
	IC693CPU313	5-Slot Base with Turbo CPU in Base (Logic Execution is .6 msec), 1K Registers, (12KBytes User Program), Not Expandable	IC693CPU367	CPU 367 Module (240KBytes Configurable User Memory), with built-in Profibus Slave (V1) Port, no built-in serial ports, Logic Execution is .22msec/K	
	IC693CPU323	10-Slot Base with Turbo CPU in Base (Logic Execution is .6 msec) 12Kbytes User Program, Not Expandable	IC693CPU370	CPU (Model 370). Requires High Capacity Power Supply	
	IC693CPU350	CPU 350 Module (74KBytes User Memory, 4K I/O, 8 Racks), No Built-In Serial Ports, Logic Execution is .22msec/K	IC693CPU372	CPU (Model 372 with built-in 10/100 Mbps Ethernet and WEB Enabled). Requires High Capacity Power Supply	
	IC693CPU360	CPU 360 Module (240KBytes Configurable User Memory, 4K I/O, 8 Racks), No Built-In Serial Ports, Logic Execution is .22msec/K	IC693CPU374 Plus	CPU 374 PLUS Module (240KBytes Configurable User Memory), No Built-In Serial Ports, Built-In 0/100Mbps with Built-In Switch (two RJ 45 ports), Logic Execution is 0.15msec/K, Ethernet Supports SRTP, EGD and Producer/Consumer Channels and Web Support; Logic Execution is .15msec/K. Requires High Capacity Power Supply	
	IC693CPU363	CPU 363 Module (240KBytes Configurable User Memory 4K I/O, 8 Racks), 2 Built-In Serial Ports, Logic Execution is .22msec/K			
Baseplates	IC693CHS391	Base, CPU, 10 Slots, Use with CPU331/CSE331 and above	IC693CHS397	Base, CPU, 5 Slots (use with CPU331/CSE331 and above)	
	IC693CHS392	Base, Expansion, 10 Slots	IC693CHS398	Base, Expansion, 5 Slots	
	IC693CHS393	Base, Remote Expansion, 10 Slots (700 ft.)	IC693CHS399	Base, Remote Expansion, 5 Slots (700 ft.)	
Power Supplies	IC693PWR321	Power Supply, 120/240 VAC, 125 VDC, Standard, 30 Watts	IC693PWR331	Power Supply, 24 VDC, High Capacity, 30 Watts	
	IC693PWR322	Power Supply, 24/48 VDC, Standard, 30 Watts	IC693PWR332	Power Supply, 12 VDC, High Capacity, 30 Watts	
	IC693PWR328	Power Supply, 48 VDC, Standard, 30 Watts	IC693ACC341	Redundant Power Supply Base with 0.5 meter cable to connect to Power Supply Adapter Module	
	IC693PWR330	Power Supply, 120/240 VAC, 125 VDC, High Capacity, 30 Watts	IC693ACC350	Redundant Power Supply Adapter (RPSA) Module. The RPSA replaces the power supply on a CPU base or expansion base and connects to a Redundant Power Supply Base.	
Accessories	IC693ACC301	Replacement Battery, CPU & PCM (Qty. 2)	IC693CBL312	Rack to Rack Expansion Cable, 0.15 Meters, Shielded	
	IC693ACC302	High Capacity Battery Pack	IC693CBL313	Rack to Rack Expansion Cable, 8 Meters	
	IC200ACC003	EZ Program Store Flash Device (for CPU374 only)	IC693CBL314	Rack to Rack Expansion Cable, 15 Meters, Shielded	
	IC693ACC310	Filler Module, Blank Slot	IC694TB032	High density terminal block, 36 box style connections.	
	IC693CBL300	Rack to Rack Expansion Cable, 1 Meter	IC694TB032	High density terminal block, 36 spring clamp connections.	
	IC693CBL301	Rack to Rack Expansion Cable, 2 Meters	IC694TB132	High density terminal block with extended shroud, 36 box style connections.	
	IC693CBL302	Rack to Rack Expansion Cable, 15 Meters	IC694TB132	High density terminal block with extended shroud, 36 spring clamp connections	
	Programming and	IC646MPP001	Proficy Logic Developer PLC Professional		
Trouble Shooting Tools	IC646MPS001	Proficy Logic Developer PLC Standard			

<sup>†</sup>Requires terminal block IC694TBxxxx.

### GE Intelligent Platforms Contact Information

Americas: 1 800 433 2682 or 1 434 978 5100

Global regional phone numbers are listed by location on our web site at [www.ge-ip.com/contact](http://www.ge-ip.com/contact)

[www.ge-ip.com](http://www.ge-ip.com)



©2010 GE Intelligent Platforms, Inc. All rights reserved.  
All other brands or names are property of their respective holders.  
Specifications are subject to change without notice.

10.10 GFA-148Q