

RC6700 Ruggedized Industrial PC



15 inch Rugged Panel PC

HAR15PFA03-48018-R01

Model: RC6700

Fanless

9Vdc to 36Vdc

UL CE SP Ex Stainless Steel SSD

Features:

- Intel® Atom™ Processor
- Completely Sealed
- IP65 Stainless Steel
- Class 1 Div 2 Certified
- ATEX 94/9/EC and CE Certified
- Wide Operating Temperature Range
- Sunlight Readable

Performance Specifications

Models	HAR15PFA03-48018-R01	
Display	15" Active Matrix TFT LCD	
Display Area	304.1 (H) x 228.1 (V) mm	
Resolution	1024 x 768 XGA	
Colors	16.2M (6bits+FRC)	
Brightness	1000 nits	
CPU	Intel® Dual Core Atom™ Processor N2600 1.6 GHz	
Chipset	Intel® Intel NM10	
System Memory	4GB DDR3 1333 MHz,	
Storage	32GB mSATA Solid State Drive	
I/O Ports	Serial	1 x RS232 (M12 connector and cable)
	USB	2 x USB 2.0 (M12 connectors and cable)
	Ethernet	1 x RJ 45-10/100/1000 Mbps (M12 connector and cable)

General Specifications

Models	HAR15PFA03-48018-R01
Input Voltage	9 - 36 Vdc m21 connector
Operation System Support	Windows Embedded Standard 7
Operating Temperature	Operating: -20°C to 60°C (-4°F to 140°F)
Certifications	CE, FCC, ISA 12.12.01-2012, Hazardous Locations Class I, Div. 2, Groups A, B, C, D, T4, CSA C22.2 NO.213-M1987, ATEX 94/9/EC, UL 60950-1
Humidity	10 to 95% RH
Operating Shock Protection	MIL-STD-810G Method 516.6
Operating Vibration Protection	MIL-STD-810G Method 514.6
External Dimensions	(W x H x D) 15.6" x 12.2" x 1.9" (396mm x 310mm x 49mm)
Warranty	Two (2) years

Ordering Information

Part Number	Description
HAR15PFA03-48018-R01	HAR15PFA03-48018-R01 Stainless Steel Panel Industrial PC with Intel Atom 2600N

Options

Part Number	Description
15-RC6700-LANCBL	LAN Cable
15-RC6700-SERCBL	Serial Cable
15-RC6700-DUSBCBL	Dual USB Cable
15-RC6700-DCACPS	DC to AC Power Adapter
15-RC6700-APWRCB	Power Cord
15-RC6700-DCPCBL	DC Power Cord flying leads

Note: All accessories listed come standard with the package

External Dimensions

