

PWS6600 Series

Display : 5.7" 320x240 ,Color/ Mono STN LCD
CPU : 32 bits RISC
Memory : 4MB Flash ROM
I/O : COM1(RS232/RS485)
 COM2 (RS232/RS422/RS485)



Hardware Specification

Model	Item					
						
	PWS6600C-N	PWS6600C-P	PWS6600C-S	PWS6600S-N	PWS6600S-P	PWS6600S-S
Replaced Models		PWS1760-CTNR	PWS1711-CTN PWS1760-CTN		PWS1760-STNR	PWS1711-STN, PWS1760-STN
LCD Type	Color STN LCD			Mono STN LCD		
Screen Size	5.7" (diagonal)					
Display Resolution	320x240					
Brightness (cd/m2)	300			110		
CPU	32 bits RISC					
Contrast Adjustment	via touch panel & VR on the back					
Display colors	256 colors			16 shades of blue		
Back Light Type	CCFT					
Back Light Life	75,000 Hours			50,000 Hours		
Operation Status LED	PWR, COM1, COM2, Ethernet LEDs					
Touch Screen	Analog					
Touch Screen (Number of Times)	>=1,000,000					
External Keypad	1 "Menu" key and 5 user-defined Function keys (F1 ... F5)					
Application Flash ROM (Bytes)	4MB					
RTC (w/ Replaceable Lithium Battery)	yes					
Data/Recipe	512 K	—	—	512 K	—	—
Data Storage (CF Card)	Under development	—	—	Under development	—	—
COM1	9-pin FEMALE (RS232/RS485)					
COM2	25-pin FEMALE (RS232/RS422/RS485)					
Multi-functional Port	26-pin connector to: Printer or 64 External Keys	—	—	26-pin connector: Printer or 64 External Keys	—	—

USB Master	Under development	—	Under development	—
USB Device	Under development	—	Under development	—
Ethernet	Yes	—	Yes	—
Network Interface Unit	OPTIONAL: Under development <input type="checkbox"/> Profibus-DP <input type="checkbox"/> CAN bus <input type="checkbox"/> DeviceNet <input type="checkbox"/> Interbus <input checked="" type="checkbox"/> LonWork			
Certification	CE			
External Dimensions	195mm x 145mm			
Cut-out Dimensions	185.8mm x 135.8mm			

Dimensions (unit:mm)

